ISO 7039:2024-07 (E)

Metallic materials - Tensile testing - Method for evaluating the susceptibility of materials to the effects of high-pressure gas within hollow test pieces

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols 2

5 Principle 2

6 Test piece 3
6.1 General 3
6.2 Shape and dimensions 3
6.3 Inner surface of hole 3
6.4 Number of test pieces 4

7 Measurement of original cross-sectional area 4

8 Marking the original gauge length 4

9 Test equipment 4
9.1 Principle 4
9.2 Testing machine 5
9.3 Extensometer 5
9.4 Test deviation 5

10 Test conditions 5
10.1 Test gas 5
10.2 Test temperature 6
10.3 Test pressure 6
10.4 Testing rate 6

11 Evaluation of the test results 6
11.1 Yield strength, tensile strength, percentage elongation after fracture with hollow test piece 6
11.2 Percentage reduction of area at leakage 7
11.3 Relative elongation after fracture with hollow test piece, Ah(rel) 7
11.4 Relative reduction of area at leakage with hollow test piece, Zh(rel) 7
11.5 Relative 0,2 % proof strength with hollow test piece, Rp0,2 h(rel) 7
11.6 Relative tensile strength with hollow test piece, Rmh(rel) 8

12 Test report 8

Bibliography 9