

ISO 21561-2:2024-08 (E)

Styrene-butadiene rubber (SBR) - Determination of the microstructure of solution-polymerized SBR - Part 2: Fourier transform infrared spectrometry (FTIR) with attenuated total reflection (ATR) method

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Apparatus	2
6	Calibration	2
6.1	FTIR	2
6.2	ATR	2
7	Sampling	2
8	Procedure for measuring ATR spectrum	3
9	Determination of the microstructure of butadiene and the styrene content	3
9.1	Measurement of the absorbance for each microstructure component	3
9.2	Calculation of microstructures	4
9.2.1	General	4
9.2.2	Base line correction of each absorbance peak	4
9.2.3	Ratio of absorbance	5
9.2.4	Second order terms	5
9.2.5	Styrene content and contents of three microstructure types of butadiene portion by regression formulae	5
9.2.6	of three microstructure types relative to butadiene portion in the S-SBR	6
10	Precision	6
11	Test report	6
Annex A (informative)	Precision results from an interlaboratory test programme	7
Annex B (informative)	Acquisition of regression formulae for microstructure	10
Annex C (informative)	Determination of microstructure by NMR spectrometry	12
Bibliography		15