

ISO 13118:2024-09 (E)

Textile - Biaxial tensile properties of woven fabric - Determination of elasticity properties using a cruciform test piece

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 3 |
| 5 | Sampling | 3 |
| 6 | Apparatus | 3 |
| 6.1 | CRE biaxial tensile testing machine | 3 |
| 7 | Atmosphere for conditioning and testing | 4 |
| 8 | Preparation of test specimens | 4 |
| 8.1 | General | 4 |
| 8.2 | Test specimen preparation | 4 |
| 9 | Procedure | 5 |
| 9.1 | Gauge length | 5 |
| 9.2 | Rate of extension | 5 |
| 9.3 | Mounting of test specimen | 5 |
| 9.4 | Loading | 5 |
| 9.5 | Operation | 5 |
| 10 | Recording | 5 |
| 11 | Calculation and expression of test results | 5 |
| 12 | Test report | 6 |
| Annex A (informative) Example of a typical cycling graph | | 8 |
| Annex B (informative) Example of a pattern for cutting test specimens from a laboratory sample | | 9 |
| Annex C (normative) Preparation of test specimen | | 10 |
| Bibliography | | 11 |