

# ISO 16826:2025-03 (E)

## Non-destructive testing - Ultrasonic testing - Testing for discontinuities perpendicular to the surface

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>Introduction</b> .....		<b>v</b>
<b>1 Scope</b> .....		<b>1</b>
<b>2 Normative references</b> .....		<b>1</b>
<b>3 Terms and definitions</b> .....		<b>1</b>
<b>4 Test equipment and test personnel</b> .....		<b>1</b>
<b>5 Tandem technique</b> .....		<b>2</b>
5.1 General.....		2
5.2 Probe movement.....		3
5.3 Time base setting.....		3
5.4 Sensitivity setting.....		3
5.5 Determination of test zones.....		4
5.6 Depth-gain diagram for tandem technique.....		5
5.7 Corrections of sensitivity.....		6
5.8 Test objects with concentric surfaces.....		6
5.8.1 General.....		6
5.8.2 Scanning on a concave surface.....		7
5.8.3 Scanning on a convex surface.....		7
<b>6 Longitudinal-longitudinal-transverse wave technique</b> .....		<b>8</b>
6.1 General.....		8
6.2 Time base setting and determination of depth of a discontinuity.....		9
6.3 Sensitivity setting.....		10
6.4 Determination of the depth of the intersection of the beam axes.....		10
6.5 Sensitivity diagram for LLT technique.....		11
6.6 Correction of sensitivity.....		11
<b>Annex A (informative) Nomograms for tandem distances for convex and concave surfaces</b> .....		<b>12</b>
<b>Bibliography</b> .....		<b>15</b>