

ISO 16827:2025-06 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities

Contents		Page
Foreword.....		iv
Introduction.....		v
1	Scope.....	1
2	Normative references.....	1
3	Terms and definitions.....	1
4	Principles of characterization of discontinuities.....	1
4.1	General.....	1
4.2	Requirements for surface condition.....	2
5	Pulse-echo techniques.....	2
5.1	General.....	2
5.2	Location of discontinuity.....	2
5.3	Orientation of discontinuity.....	3
5.4	Assessment of multiple indications.....	3
5.5	Shape of discontinuity.....	4
5.5.1	Simple classification.....	4
5.5.2	Detailed classification.....	4
5.6	Maximum echo height of indication.....	5
5.7	Size of discontinuity.....	5
5.7.1	General.....	5
5.7.2	Maximum echo height techniques.....	5
5.7.3	Probe movement sizing techniques.....	6
5.7.4	Selection of sizing techniques.....	7
5.7.5	Sizing techniques with focusing probes.....	8
5.7.6	Use of mathematical algorithms for sizing.....	8
5.7.7	Special sizing techniques.....	8
6	Through-transmission technique.....	9
6.1	General.....	9
6.2	Location of discontinuity.....	9
6.3	Evaluation of multiple discontinuities.....	9
6.4	Reduction of signal amplitude.....	10
6.5	Size of discontinuity.....	10
Annex A (normative)	Analysis of multiple indications.....	12
Annex B (normative)	Techniques for the classification of discontinuity shape.....	14
Annex C (normative)	Sizing technique using the maximum echo height.....	23
Annex D (normative)	Sizing techniques using probe movement.....	25
Annex E (informative)	Iterative sizing technique.....	37
Annex F (informative)	Mathematical algorithms for the estimation of the actual size of a discontinuity.....	41
Annex G (informative)	Examples of special sizing techniques.....	47
Bibliography.....		50