

ISO 16827:2025-06 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principles of characterization of discontinuities	1
4.1	General	1
4.2	Requirements for surface condition	2
5	Pulse-echo techniques	2
5.1	General	2
5.2	Location of discontinuity	2
5.3	Orientation of discontinuity	3
5.4	Assessment of multiple indications	3
5.5	Shape of discontinuity	4
5.5.1	Simple classification	4
5.5.2	Detailed classification	4
5.6	Maximum echo height of indication	5
5.7	Size of discontinuity	5
5.7.1	General	5
5.7.2	Maximum echo height techniques	5
5.7.3	Probe movement sizing techniques	6
5.7.4	Selection of sizing techniques	7
5.7.5	Sizing techniques with focusing probes	8
5.7.6	Use of mathematical algorithms for sizing	8
5.7.7	Special sizing techniques	8
6	Through-transmission technique	9
6.1	General	9
6.2	Location of discontinuity	9
6.3	Evaluation of multiple discontinuities	9
6.4	Reduction of signal amplitude	10
6.5	Size of discontinuity	10
Annex A (normative)	Analysis of multiple indications	12
Annex B (normative)	Techniques for the classification of discontinuity shape	14
Annex C (normative)	Sizing technique using the maximum echo height	23
Annex D (normative)	Sizing techniques using probe movement	25
Annex E (informative)	Iterative sizing technique	37
Annex F (informative)	Mathematical algorithms for the estimation of the actual size of a discontinuity	41
Annex G (informative)	Examples of special sizing techniques	47
Bibliography		50