

DIN EN ISO 16827:2025-09 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2025)

Contents		Page
Foreword.....		iv
Introduction.....		v
1 Scope.....		1
2 Normative references.....		1
3 Terms and definitions.....		1
4 Principles of characterization of discontinuities.....		1
4.1 General.....		1
4.2 Requirements for surface condition.....		2
5 Pulse-echo techniques.....		2
5.1 General.....		2
5.2 Location of discontinuity.....		2
5.3 Orientation of discontinuity.....		3
5.4 Assessment of multiple indications.....		3
5.5 Shape of discontinuity.....		4
5.5.1 Simple classification.....		4
5.5.2 Detailed classification.....		4
5.6 Maximum echo height of indication.....		5
5.7 Size of discontinuity.....		5
5.7.1 General.....		5
5.7.2 Maximum echo height techniques.....		5
5.7.3 Probe movement sizing techniques.....		6
5.7.4 Selection of sizing techniques.....		7
5.7.5 Sizing techniques with focusing probes.....		8
5.7.6 Use of mathematical algorithms for sizing.....		8
5.7.7 Special sizing techniques.....		8
6 Through-transmission technique.....		9
6.1 General.....		9
6.2 Location of discontinuity.....		9
6.3 Evaluation of multiple discontinuities.....		9
6.4 Reduction of signal amplitude.....		10
6.5 Size of discontinuity.....		10
Annex A (normative) Analysis of multiple indications		12
Annex B (normative) Techniques for the classification of discontinuity shape		14
Annex C (normative) Sizing technique using the maximum echo height		23
Annex D (normative) Sizing techniques using probe movement		25
Annex E (informative) Iterative sizing technique		37
Annex F (informative) Mathematical algorithms for the estimation of the actual size of a discontinuity		41
Annex G (informative) Examples of special sizing techniques		47
Bibliography		50