

ISO 16828:2025-07 (E)

Non-destructive testing - Ultrasonic testing - Time-of-flight diffraction technique for detection and sizing of discontinuities

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	2
5	General	3
5.1	Principle of the technique	3
5.2	Requirements for surface condition and couplant	5
5.3	Materials and process type	5
6	Qualification of test personnel	5
7	Requirements for test equipment	6
7.1	General	6
7.2	Instrument and display	6
7.3	Probes	8
7.4	Scanning	8
8	TOFD setup procedures	9
8.1	General	9
8.2	Probe selection and probe separation	9
8.2.1	Probe selection	9
8.2.2	Probe separation	10
8.3	Time window setting	10
8.4	Sensitivity setting	10
8.5	Scan increment setting	10
8.6	Setting of scanning speed	11
8.7	Checking of system performance	11
9	Interpretation and analysis of data	11
9.1	Basic analysis of discontinuities	11
9.1.1	General	11
9.1.2	Characterization of discontinuities	12
9.1.3	Estimation of discontinuity position	12
9.1.4	Estimation of discontinuity length	13
9.1.5	Estimation of discontinuity depth and height	13
9.2	Detailed analysis of discontinuities	14
9.2.1	General	14
9.2.2	Additional scans	14
9.2.3	Additional algorithms	15
10	Detection and sizing in complex geometries	16
11	Limitations of the TOFD technique	16

11.1	General	16
11.2	Accuracy and resolution	17
11.2.1	General	17
11.2.2	Inaccuracy in the lateral position	17
11.2.3	Timing inaccuracy	17
11.2.4	Inaccuracy in sound velocity	17
11.2.5	Inaccuracy in probe centre separation	17
11.2.6	Spatial resolution	18
11.3	Obscured zones	18
12	TOFD testing without data recording	19
13	Test procedure	19
14	Test report	19
Annex A (informative) Reference blocks		20
Bibliography		21