

DIN EN ISO 16828:2025-11 (E)

Non-destructive testing - Ultrasonic testing - Time-of-flight diffraction technique for detection and sizing of discontinuities (ISO 16828:2025)

Contents

	Page
Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Symbols and units.....	2
5 General.....	3
5.1 Principle of the technique.....	3
5.2 Requirements for surface condition and couplant.....	5
5.3 Materials and process type.....	5
6 Qualification of test personnel.....	5
7 Requirements for test equipment.....	6
7.1 General.....	6
7.2 Instrument and display.....	6
7.3 Probes.....	8
7.4 Scanning.....	8
8 TOFD setup procedures.....	9
8.1 General.....	9
8.2 Probe selection and probe separation.....	9
8.2.1 Probe selection.....	9
8.2.2 Probe separation.....	10
8.3 Time window setting.....	10
8.4 Sensitivity setting.....	10
8.5 Scan increment setting.....	10
8.6 Setting of scanning speed.....	11
8.7 Checking of system performance.....	11
9 Interpretation and analysis of data.....	11
9.1 Basic analysis of discontinuities.....	11
9.1.1 General.....	11
9.1.2 Characterization of discontinuities.....	12
9.1.3 Estimation of discontinuity position.....	12
9.1.4 Estimation of discontinuity length.....	13
9.1.5 Estimation of discontinuity depth and height.....	13
9.2 Detailed analysis of discontinuities.....	14
9.2.1 General.....	14
9.2.2 Additional scans.....	14
9.2.3 Additional algorithms.....	15
10 Detection and sizing in complex geometries.....	16
11 Limitations of the TOFD technique.....	16
11.1 General.....	16
11.2 Accuracy and resolution.....	17
11.2.1 General.....	17
11.2.2 Inaccuracy in the lateral position.....	17

11.2.3 Timing inaccuracy 17
11.2.4 Inaccuracy in sound velocity 17
11.2.5 Inaccuracy in probe centre separation 17
11.2.6 Spatial resolution 18
11.3 Obscured zones 18
12 TOFD testing without data recording 19
13 Test procedure 19
14 Test report 19
Annex A (informative) Reference blocks 20
Bibliography 21