

ISO 24251-1:2025-08 (E)

Prevention of hydrogen assisted brittle fracture of high-strength steel components - Part 1: Fundamentals and measures

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 4 |
| 5 | Fundamentals | 5 |
| 5.1 | General description of hydrogen embrittlement | 5 |
| 5.2 | Conditions for hydrogen embrittlement failure | 5 |
| 5.2.1 | General | 5 |
| 5.2.2 | Material susceptibility | 6 |
| 5.2.3 | Tensile stress | 7 |
| 5.2.4 | Sources of atomic hydrogen | 7 |
| 5.3 | Mechanism of hydrogen embrittlement of high strength steel | 8 |
| 5.4 | Fundamentals of metallic coatings regarding hydrogen uptake and diffusion | 9 |
| 5.4.1 | General aspects of metallic electroplated protection layers | 9 |
| 5.4.2 | Hydrogen generation during coating process | 9 |
| 5.4.3 | Corrosion protection mechanisms by metallic layers | 9 |
| 6 | Preventive measures with regard to hydrogen embrittlement | 12 |
| 6.1 | General | 12 |
| 6.2 | Part design and manufacturing | 13 |
| 6.3 | Material related measures and heat treatment | 13 |
| 6.4 | Reduction of residual tensile stress (stress relief) | 14 |
| 6.5 | Measures related to coating processes | 14 |
| 6.5.1 | General | 14 |
| 6.5.2 | Pre-treatment -- Cleaning processes | 15 |
| 6.5.3 | Electroplating coating processes | 15 |
| 6.5.4 | Stripping of coatings | 15 |
| 6.5.5 | Corrective actions - Baking | 16 |
| 6.6 | Prevention of environmental hydrogen uptake | 17 |
| 6.6.1 | General | 17 |
| 6.6.2 | Environmentally appropriate design | 17 |
| Annex A (informative) Electroplating processes | | 18 |
| Annex B (informative) Principles of electrochemical corrosion | | 20 |
| Bibliography | | 23 |