

DIN EN 15365:2026-02 (E)

Advanced technical ceramics - Mechanical properties of ceramic fibres at high temperature in a non-reactive environment - Determination of creep behaviour by the cold grip method

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Principle | 7 |
| 5 | Significance and use | 9 |
| 6 | Apparatus | 9 |
| 6.1 | Test installations | 9 |
| 6.2 | Load train | 9 |
| 6.3 | Test chamber | 9 |
| 6.4 | Set-up for heating | 10 |
| 6.5 | Temperature measurement | 10 |
| 6.6 | Control of deformation | 10 |
| 6.7 | Data recording system | 10 |
| 6.8 | Determination of fibre cross-sectional area | 10 |
| 7 | Test specimens | 10 |
| 7.1 | Test specimen preparation | 10 |
| 7.2 | Number of test specimens | 12 |
| 8 | Test procedures | 12 |
| 8.1 | Determination of the temperature profile in the furnace | 12 |
| 8.2 | Test set-up: Determination of the temperature profile and of the different lengths of each temperature zone in the furnace | 12 |
| 8.3 | Test set-up: Loading considerations | 12 |
| 8.4 | Test technique | 12 |
| 8.4.1 | Specimen mounting | 12 |
| 8.4.2 | Setting of an inert environment | 12 |
| 8.4.3 | Heating of the test specimen | 13 |
| 8.4.4 | Measurements | 13 |
| 8.4.5 | Monitoring of temperature stability | 14 |
| 8.5 | Test validity | 14 |
| 9 | Calculation of results | 14 |
| 9.1 | Creep stress | 14 |
| 9.2 | Creep strain at time t | 15 |
| 9.2.1 | Reading of the longitudinal deformation | 15 |
| 9.2.2 | Calculation of the deformation due to the creep | 15 |
| 9.2.3 | Drawing of the creep curve | 15 |
| 9.2.4 | Creep strain at rupture | 15 |
| 9.2.5 | Creep rupture time | 15 |
| 9.2.6 | Creep strain rate curve | 15 |

| | | |
|---------------------------|--------------------------|-----------|
| 10 | Test report | 16 |
| Bibliography | | 17 |