

# ISO 13935-2:2026-04 (E)

## Textiles - Seam tensile properties of fabrics and made-up textile articles - Part 2: Determination of maximum force to seam rupture using the grab method

---

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Principle</b> .....	<b>2</b>
<b>5 Sampling</b> .....	<b>2</b>
<b>6 Apparatus</b> .....	<b>3</b>
6.1 CRE machine.....	3
6.2 Equipment for sewing defined seams.....	4
6.3 Equipment for cutting test specimens.....	4
<b>7 Atmosphere for conditioning and testing</b> .....	<b>4</b>
<b>8 Preparation of seams and of test specimens</b> .....	<b>4</b>
8.1 Preparation of seams, if required, before testing.....	4
8.2 Preparation of adjacent test specimens from one laboratory sample.....	4
8.3 Preparation of test specimens.....	5
<b>9 Procedure</b> .....	<b>7</b>
9.1 Gauge length.....	7
9.2 Rate of extension.....	7
9.3 Mounting of test specimens.....	7
9.4 Operation.....	7
<b>10 Calculation and expression of results</b> .....	<b>7</b>
<b>11 Test report</b> .....	<b>8</b>
<b>Annex A (informative) Arrangements of jaws for the grab test</b> .....	<b>9</b>
<b>Annex B (informative) Considerations on straight seams and sampling of structural seams on garments</b> .....	<b>10</b>
<b>Bibliography</b> .....	<b>13</b>