

# ISO 13935-2:2026-04 (E)

## Textiles - Seam tensile properties of fabrics and made-up textile articles - Part 2: Determination of maximum force to seam rupture using the grab method

---

| <b>Contents</b>   | <b>Page</b> |
|---|-------------|
| Foreword.....   | iv          |
| Introduction.....   | v           |
| <b>1 Scope.....</b>   | <b>1</b>    |
| <b>2 Normative references.....</b>  | <b>1</b>    |
| <b>3 Terms and definitions.....</b>   | <b>1</b>    |
| <b>4 Principle.....</b>   | <b>2</b>    |
| <b>5 Sampling.....</b>  | <b>2</b>    |
| <b>6 Apparatus.....</b>   | <b>3</b>    |
| 6.1 CRE machine.....  | 3           |
| 6.2 Equipment for sewing defined seams.....   | 4           |
| 6.3 Equipment for cutting test specimens.....   | 4           |
| <b>7 Atmosphere for conditioning and testing.....</b>   | <b>4</b>    |
| <b>8 Preparation of seams and of test specimens.....</b>  | <b>4</b>    |
| 8.1 Preparation of seams, if required, before testing.....  | 4           |
| 8.2 Preparation of adjacent test specimens from one laboratory sample.....                                      | 4           |
| 8.3 Preparation of test specimens.....  | 5           |
| <b>9 Procedure.....</b>   | <b>7</b>    |
| 9.1 Gauge length.....   | 7           |
| 9.2 Rate of extension.....  | 7           |
| 9.3 Mounting of test specimens.....   | 7           |
| 9.4 Operation.....  | 7           |
| <b>10 Calculation and expression of results.....</b>  | <b>7</b>    |
| <b>11 Test report.....</b>  | <b>8</b>    |
| <b>Annex A (informative) Arrangements of jaws for the grab test.....</b>  | <b>9</b>    |
| <b>Annex B (informative) Considerations on straight seams and sampling of structural seams on garments.....</b> | <b>10</b>   |
| <b>Bibliography.....</b>  | <b>13</b>   |