ISO 20198:2026-05 (E)

Metallic materials - Steel - Method of test for the determination of brittle crack arrest temperature (CAT)

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols 2

5 Test equipment 2
5.1 General 2
5.2 Testing machine 3
5.2.1 Force implementation 3
5.2.2 Calibration of the testing machine 3
5.2.3 Loading direction 3
5.2.4 Loading distance 3
5.3 Methods for initiating brittle cracks 3
5.3.1 Impact type method 3
5.3.2 Double tension tab plate type method 3

6 Test pieces 3
6.1 Configurations and dimensions of test pieces with side grooves 3
6.1.1 General 3
6.1.2 Side grooves 4
6.1.3 Number of test pieces 4
6.2 Configurations of extension plates and tab plates 5
6.2.1 General 5
6.2.2 Extension plates 5
6.2.3 Tab plates 5
6.3 Welding of test piece and extension plates 5
6.4 Impact type crack initiation 6
6.5 Double tension type crack initiation 6
6.6 Embrittled zone setting 6
6.7 Side grooves for embrittled zone preparation 7
6.8 Regulation of embrittled zone 7

7 Test method 8
7.1 Pre-loading 8
7.2 Temperature measurement and control 8
7.2.1 Temperature control plan 8
7.2.2 Temperature measurement 8
7.2.3 EBW embrittlement 9
7.2.4 LTG embrittlement 9
7.2.5 Double tension type crack initiation test piece 12
7.3 Loading and brittle crack initiation 12

8 Test procedures 12
8.1 Pre-test procedures 12

8.2 Impacting procedures 13
8.3 Procedures after testing 13
8.4 Observation of fracture surfaces 13

9 Test validation judgement, judgement of "arrest" or "propagate" and CAT determination 14
9.1 Brittle crack initiation and validation 14
9.2 Crack path examination and validation 15
9.3 Fracture surface examination, crack length measurement and validation 15
9.4 Final test judgement of "arrest", "propagate" or "invalid" 16
9.5 Ttest, Tarrest and CAT determination 17
9.5.1 Test determination 17
9.5.2 Target determination 17
9.5.3 CAT determination 17

10 Test report 17

Bibliography 19