

ISO 16659-3:2026-06 (E)

Ventilation systems for nuclear facilities - In-situ efficiency test methods for iodine traps with solid sorbent - Part 3: Cyclohexane gas leakage rate method

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Method.....	2
4.1 Scope of the method.....	2
4.2 Principle of the method.....	2
4.3 Parameters affecting the achievements.....	3
4.3.1 General.....	3
4.3.2 Relative humidity.....	4
4.3.3 Influence of contact time between air and the sorbent (air velocity).....	4
4.3.4 Temperature.....	5
4.3.5 Particulate size and density.....	5
4.3.6 Initial tracer gas concentration.....	5
4.4 Other specificities of the method.....	5
5 Test equipment.....	5
5.1 Injection device.....	5
5.1.1 Test medium.....	5
5.1.2 Generators of cyclohexane gas.....	6
5.2 Measurement device.....	8
5.2.1 Concentration (gas chromatograph/VOC detector with a PID detector).....	8
5.2.2 Relative humidity (hygrometer).....	9
5.2.3 Ventilation flow rate (anemometer).....	9
5.2.4 Temperature (thermometer).....	9
6 Safety of workers, the public, and the environment.....	9
6.1 Facility arrangements.....	9
6.2 Main safety provisions for workers.....	10
6.3 Environment safety provisions.....	10
6.4 Management of cyclohexane.....	10
7 Mode of performing the test.....	10
7.1 Test preparation.....	10
7.2 Test execution.....	11
7.3 Other specificities.....	12
8 Establishment of the test result.....	12
8.1 Expression of the test result.....	12
8.2 Accuracy of the result.....	13
8.3 Evaluation and test report.....	13
8.3.1 Leakage rate test of iodine absorber.....	13
8.3.2 Performance test of absorbent.....	14
Annex A (informative) Schematic layout of the method of test.....	15
Annex B (informative) Example text for test report.....	16
Bibliography.....	17

Annex B (informative) Example text for test report	16
Bibliography	17