

# ISO 15169:2003-12 (E)

## Petroleum and liquid petroleum products - Determination of volume, density and mass of the hydrocarbon content of vertical cylindrical tanks by hybrid tank measurement systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>General precautions .....</b>	<b>2</b>
<b>4.1</b>	<b>Safety precautions .....</b>	<b>2</b>
<b>4.2</b>	<b>Equipment precautions .....</b>	<b>3</b>
<b>5</b>	<b>Selection and installation of hybrid tank measurement system equipment .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Automatic level gauge .....</b>	<b>4</b>
<b>5.3</b>	<b>Pressure sensor(s) .....</b>	<b>4</b>
<b>5.4</b>	<b>Automatic tank thermometer (ATT) .....</b>	<b>5</b>
<b>5.5</b>	<b>Hybrid processor .....</b>	<b>5</b>
<b>5.6</b>	<b>Optional sensors .....</b>	<b>6</b>
<b>6</b>	<b>Accuracy effects of HTMS components .....</b>	<b>6</b>
<b>6.1</b>	<b>General .....</b>	<b>6</b>
<b>6.2</b>	<b>Accuracy effects of the ALG .....</b>	<b>6</b>
<b>6.3</b>	<b>Accuracy effects of the pressure sensor(s) .....</b>	<b>7</b>
<b>6.4</b>	<b>Accuracy effects of the ATT .....</b>	<b>7</b>
<b>7</b>	<b>HTMS measurement and calculations .....</b>	<b>8</b>
<b>7.1</b>	<b>General .....</b>	<b>8</b>
<b>7.2</b>	<b>HTMS Mode 1 .....</b>	<b>8</b>
<b>7.3</b>	<b>HTMS Mode 2 .....</b>	<b>8</b>
<b>8</b>	<b>Commissioning and initial field calibration .....</b>	<b>8</b>
<b>8.1</b>	<b>General .....</b>	<b>8</b>
<b>8.2</b>	<b>Initial preparation .....</b>	<b>9</b>
<b>8.3</b>	<b>Initial calibration and verification of HTMS components .....</b>	<b>9</b>
<b>8.4</b>	<b>Verification of hybrid processor calculations .....</b>	<b>10</b>
<b>8.5</b>	<b>Initial field verification of HTMS .....</b>	<b>10</b>
<b>9</b>	<b>Subsequent verification .....</b>	<b>11</b>
<b>9.1</b>	<b>General .....</b>	<b>11</b>
<b>9.2</b>	<b>Objectives .....</b>	<b>12</b>
<b>9.3</b>	<b>Adjustment during regular verification .....</b>	<b>12</b>
<b>9.4</b>	<b>Subsequent verification of HTMS in volume-based custody transfer application .....</b>	<b>12</b>
<b>9.5</b>	<b>Subsequent verification of HTMS in mass-based custody transfer applications .....</b>	<b>13</b>
<b>9.6</b>	<b>Handling out-of-tolerance situations during regular verification of HTMS in custody transfer application .....</b>	<b>14</b>
<b>Annex A (informative)</b>	<b>Calculation overview .....</b>	<b>17</b>
<b>Annex B (informative)</b>	<b>Measurement accuracy and uncertainty analysis .....</b>	<b>21</b>