

ISO 15169:2003-12 (E)

Petroleum and liquid petroleum products - Determination of volume, density and mass of the hydrocarbon content of vertical cylindrical tanks by hybrid tank measurement systems

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 General precautions	2
4.1 Safety precautions	2
4.2 Equipment precautions	3
5 Selection and installation of hybrid tank measurement system equipment	3
5.1 General	3
5.2 Automatic level gauge	4
5.3 Pressure sensor(s)	4
5.4 Automatic tank thermometer (ATT)	5
5.5 Hybrid processor	5
5.6 Optional sensors	6
6 Accuracy effects of HTMS components	6
6.1 General	6
6.2 Accuracy effects of the ALG	6
6.3 Accuracy effects of the pressure sensor(s)	7
6.4 Accuracy effects of the ATT	7
7 HTMS measurement and calculations	8
7.1 General	8
7.2 HTMS Mode 1	8
7.3 HTMS Mode 2	8
8 Commissioning and initial field calibration	8
8.1 General	8
8.2 Initial preparation	9
8.3 Initial calibration and verification of HTMS components	9
8.4 Verification of hybrid processor calculations	10
8.5 Initial field verification of HTMS	10
9 Subsequent verification	11
9.1 General	11
9.2 Objectives	12
9.3 Adjustment during regular verification	12
9.4 Subsequent verification of HTMS in volume-based custody transfer application	12
9.5 Subsequent verification of HTMS in mass-based custody transfer applications	13
9.6 Handling out-of-tolerance situations during regular verification of HTMS in custody transfer application	14
Annex A (informative) Calculation overview	17
Annex B (informative) Measurement accuracy and uncertainty analysis	21