

# ISO 17874-2:2004-12 (E)

## Remote-handling devices for radioactive materials - Part 2: Mechanical master-slave manipulators

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General architecture and classification .....</b>	<b>3</b>
4.1	General architecture .....	3
4.2	Classification .....	4
4.3	Kinematics .....	7
<b>5</b>	<b>Basic considerations for the choice of a manipulator .....</b>	<b>9</b>
5.1	General criteria .....	9
5.2	Particular criteria .....	10
5.3	Mounting of the master-slave manipulators .....	12
5.4	Leak-tightness and protection against contamination .....	13
<b>6</b>	<b>Different manipulator mounting methods and associated requirements .....</b>	<b>15</b>
6.1	Unsealed connection tube, with a gaiter .....	15
6.2	Unsealed connection tube, without gaiter .....	21
6.3	Sealed connection tube .....	21
6.4	Design of the lower end of the gaiters .....	22
6.5	Special case of double gaiters .....	25
6.6	Replacement of manipulator gaiters .....	26
6.7	Attachment of leak-tight manipulator gaiters .....	29
<b>7</b>	<b>Accessories .....</b>	<b>29</b>
7.1	Connection tubes with shielding .....	29
7.2	Balancing .....	29
7.3	Terminations .....	30
7.4	Electricity supply .....	31
7.5	Various .....	31
<b>Annex A (normative)</b>	<b>Method of measurement of no-load forces and torques, flexures and backlashes .....</b>	<b>33</b>
<b>Annex B (informative)</b>	<b>Typical disconnection stations .....</b>	<b>45</b>
<b>Bibliography .....</b>		<b>48</b>