DIN 51309:2005-12 (E)

Materials testing machines - Calibration of static torque measuring devices

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Symbols 5

4 Characteristics of the torque measuring instrument 7
4.1 Description and marking of the torque measuring instrument 7
4.2 Inducing the torque 7
4.3 Measurement of the torque by deformation 7

5 Calibration of the torque measuring instrument 7
5.1 General 7
5.1.1 Requirements 7
5.1.2 Overload check 8
5.2 Resolution of the display unit 8
5.2.1 Scale indication 8
5.2.2 Numeric display 8
5.2.3 Indication fluctuation 8
5.2.4 Units 8
5.2.5 Measurement range initial value 8
5.3 Preparation of the calibration 8
5.3.1 Display unit 8
5.3.2 Temperature equalization 9
5.3.3 Transducer zero value ls 9
5.3.4 Installation direction, transducer connection 9
5.4 Carrying out the calibration 9
5.4.1 Scope of the calibration and procedure 9
5.4.2 Preloading 10
5.4.3 Installation position 10
5.4.4 Carrying out the calibration 10
5.4.5 Loading conditions 11
5.4.6 Displayed value corrected for the zero value Xj(MK) 11
5.4.7 Evaluation of the torque measuring instruments 11
5.4.8 Short-time creeping 14

6 Classification of the torque measuring instrument 14
6.1 Classification principle 14
6.2 Measurement range initial value and classification criteria 14
6.2.1 Measurement range initial value 14
6.2.2 Classification criteria 14
6.3 Calibration certificate and recalibration 15
6.3.1 Calibration certificate 15
6.3.2 Recalibration 16

7 Standard designation 16

Annex A (normative) Application of calibrated torque measuring instruments 17

Annex B (informative) Recommended dimensions for torque transducers, including couplings for their adaptation in torque calibrators 18

Annex C (informative) Determination of the relative expanded measurement uncertainty W for the calibration of torque measuring instruments 19

C.1 Determination of the measurement uncertainty of the interpolated calibration result for the calibration of torque measuring instruments 19
C.1.1 Model 19
C.1.2 Measurement uncertainty budget 20

Annex D (informative) Calibration procedure 24

Annex E (informative) Features for measurement of vibratory torque 25

Bibliography 27

List of figures Figure B.1 18

Figure D.1 -- Example of the preloadings and measurement series for the classes 0,05 and 0,1 24

Figure D.2 -- Example of the preloadings and measurement series of square drive transducers for the classes 0,2 and 0,5 24

Figure D.3 -- Example of the preloadings and measurement series of square drive transducers for the classes 1 to 5 24

Figure E.1 -- Interpolation deviations for clockwise and anti-clockwise torque, related to the corresponding zero points (here and in the following, filled symbols signify: increasing value of the torque; blank symbols: decreasing value) 25

Figure E.2 -- Interpolation deviations for alternating torque with integrated contours for clockwise and anti-clockwise torque, related to the mean value of the associated zero points 26

Figure E.3 -- Range of the interpolation deviation (thick line) for an alternating torque transducer with unknown history 26

List of tables Table 1 -- Symbols, units and designation 5

Table 2 -- Number of series of measurements required 10

Table 3 -- Classification characteristics of the torque measuring instruments 15

Table B.1 18

Table C.1 -- Distribution functions for the calculation of the relative standard deviations for the parameters calculated from the ranges determined from experiment 20

Table C.2 -- Example for the tabular calculation of the relative standard measurement uncertainty w for torque measuring instruments for static torques 23