

DIN EN 15158:2006-10 (E)

Advanced technical ceramics - Mechanical properties of ceramic composites at high temperature under inert atmosphere - Determination of fatigue properties at constant amplitude

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms, definitions and symbols | 5 |
| 4 | Principle | 8 |
| 5 | Significance and use | 8 |
| 6 | Apparatus | 9 |
| 6.1 | Fatigue test machine | 9 |
| 6.2 | Load train | 9 |
| 6.3 | Test chamber | 10 |
| 6.4 | Set-up for heating | 10 |
| 6.5 | Extensometer | 10 |
| 6.6 | Temperature measurement | 11 |
| 6.7 | Data recording system | 11 |
| 6.8 | Micrometers | 11 |
| 7 | Test specimens | 11 |
| 8 | Test specimen preparation | 12 |
| 8.1 | Machining and preparation | 12 |
| 8.2 | Number of test specimens | 12 |
| 9 | Test procedure | 12 |
| 9.1 | Test set-up: temperature considerations | 12 |
| 9.2 | Measurement of test specimen dimensions | 13 |
| 9.3 | Testing technique | 13 |
| 9.4 | Test validity | 14 |
| 10 | Calculation of results | 15 |
| 10.1 | Time to failure, t_f | 15 |
| 10.2 | Damage parameters | 15 |
| 10.3 | Residual properties | 17 |
| 11 | Test report | 17 |
| Annex A (informative) | Schematic evolution of E | 18 |