ISO 7507-3:2006-07 (E)

Petroleum and liquid petroleum products - Calibration of vertical cylindrical tanks - Part 3: Optical-triangulation method

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Precautions 1

5 Equipment 2
5.1 Equipment for measurement of angles 2
5.2 Stadia 2

6 Equipment set-up and procedure 2
6.1 Preparation of tank 2
6.2 Establishment of calibration conditions 2
6.3 Set-up of theodolites and/or total stations 3

7 Stadia set-up and procedure 3

8 Measurement of horizontal distance between two theodolite stations using a stadia 3

9 Measurement of horizontal distance between two theodolite stations using a total station 5

10 Procedure for internal optical tank wall measurements 5

11 Procedures for external measurements 8
11.1 General 8
11.2 Reference circumference measured by strapping 8
11.3 Reference distances measured between pairs of theodolite stations 10

12 Tolerances 11
12.1 Distances between theodolites 11
12.2 Horizontal angles 11
12.3 Reference circumference 11

13 Other measurements for tank calibrations 12
13.1 Tank-bottom calibrations 12
13.2 Other measurements and data 12

14 Calculations and development of tank capacity tables 13
14.1 From the internal procedure 13
14.2 From the reference circumference procedure 13
14.3 From the reference distances between pairs of theodolites 13
14.4 Corrections 13
14.5 Tank capacity table 13

Annex A (normative) Computation of internal radii from internal measurements 14

Annex B (normative) Determination of the radius of the circle by the least-squares method 15

Annex C (normative) Computation of internal radii from reference circumference and external measurements 20

Annex D (normative) Computation of internal radii from reference distances between pairs of theodolite stations 22

Annex E (informative) Calibration uncertainties 24

Annex F (normative) Procedure for checking the theodolite(s) 36

Bibliography 38