

# ISO 4664-2:2006-10 (E)

## Rubber, vulcanized or thermoplastic - Determination of dynamic properties - Part 2: Torsion pendulum methods at low frequencies

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>1</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
5.1	Test piece holder .....	2
5.2	Inertial member .....	2
5.3	Torsion pendulum .....	2
5.4	Thermostatted test chamber .....	6
5.5	Devices for measurement of test piece dimensions .....	6
<b>6</b>	<b>Test pieces .....</b>	<b>6</b>
6.1	Dimensions .....	6
6.2	Preparation .....	6
6.3	Number .....	6
6.4	Conditioning .....	6
<b>7</b>	<b>Strain, frequency and temperature of test .....</b>	<b>7</b>
7.1	Strain .....	7
7.2	Frequency .....	7
7.3	Temperature .....	7
<b>8</b>	<b>Procedure .....</b>	<b>7</b>
8.1	Measurement of dimensions of test piece .....	7
8.2	Mechanical conditioning of test piece .....	7
8.3	Mounting of test piece .....	8
8.4	Measurement of test piece free length .....	8
8.5	Temperature conditioning of test piece .....	8
8.6	Testing .....	8
<b>9</b>	<b>Expression of results .....</b>	<b>9</b>
9.1	Symbols .....	9
9.2	Calculation of the elastic shear modulus (in-phase modulus) .....	9
9.3	Calculation of mechanical damping .....	10
<b>10</b>	<b>Test report .....</b>	<b>11</b>
Bibliography .....		12