

DIN EN ISO 24817:2025-10 (E)

Erscheinungsdatum: 2025-08-29

Petroleum, petrochemical and natural gas industries - Composite repairs for pipework - Qualification and design, installation, testing and integrity management (ISO/DIS 24817:2025); English version prEN ISO 24817:2025

Contents

	Page
Foreword.....	vi
Introduction.....	vii
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Symbols and abbreviated terms.....	7
4.1 Units.....	7
4.2 Symbols.....	7
4.3 Abbreviated terms.....	11
5 Applications.....	11
6 Summary of key issues.....	13
6.1 Repair system qualification.....	14
6.2 Enquiry stage.....	14
6.3 Design of repair.....	14
6.3.1 Type A and Type B design cases.....	14
6.4 Installer training.....	17
6.5 Installation of repair.....	17
6.6 Ongoing integrity management of the repaired system.....	17
7 Qualification.....	17
7.1 Repair system qualification data.....	17
7.2 Re-qualification of the repair system.....	19
7.2.1 Overview.....	19
7.2.2 For Type A defect repairs.....	19
7.2.3 For Type B defect repairs.....	19
8 Repair feasibility assessment.....	19
8.1 Repair class.....	21
8.2 Required data.....	21
8.2.1 Background.....	21
8.2.2 Original equipment design data.....	21
8.2.3 Maintenance and operational histories.....	22
8.2.4 Service condition data.....	22
9 Design methodology.....	22
9.1 Repair design lifetime and initial service life.....	22
9.2 Environmental compatibility.....	23
9.3 Design temperature effects.....	23
9.4 Cyclic loading.....	25
9.5 Determination of design strains.....	25
9.5.1 Design strains based on default allowable strains.....	25
9.5.2 Design strains based on performance testing.....	26
9.6 Determination of equivalent load and equivalent pressure.....	26
9.7 Design of repairs for Type A defects.....	27
9.7.1 Substrate load sharing, limited by substrate allowable stress.....	27
9.7.2 Substrate load sharing, limited by repair laminate design strain.....	27
9.7.3 Repair laminate carries all loads.....	28
9.8 Design of repairs for Type B defects.....	28

9.8.1	Determination of service factor, f_{leak}	29
9.8.2	Circular or near-circular defects	29
9.8.3	Slot-type defects in the circumferential direction	30
9.8.4	Slot-type defects in the axial direction	30
9.9	External loads	30
9.10	Other defects (with assessments based on substrate stress)	31
9.11	Repair of other components	31
9.12	Axial extent of repair	32
9.12.1	Patches	33
9.13	Calculation of the repair design thickness, t_{design}	34
9.14	Confirmation that repair design thickness is within acceptable limits	34
9.14.1	Maximum acceptable value of t_{calc}	34
9.14.2	Maximum allowable design pressure for tees or nozzles	34
9.14.3	Potential for repair debonding	34
9.15	Calculation of total repair length	35
9.16	Design output	36
9.17	Optional design considerations	36
9.17.1	Fire performance	36
9.17.2	Cathodic disbondment	36
9.17.3	Electrical conductivity	37
9.17.4	Fretting type defects	37
9.17.5	Delamination or blister type defects	37
9.17.6	Clamps and other repair systems	37
10	Installation	37
10.1	Storage conditions	37
10.2	Documentation prior to repair application	38
10.2.1	Method statement	38
10.2.2	Work pack	38
10.3	Installer and supervisor qualifications	40
10.4	Installation procedure	40
10.5	Repair completion documentation	40
10.6	Live repairs	42
10.7	Repair of clamps, piping components, tanks, or vessels	42
10.8	Environmental considerations	42
10.9	Repair of defects within the repair system	42
11	Ongoing integrity management	43
11.1	General	43
11.2	Record keeping	43
11.3	In-service inspection	43
11.4	Allowable defects for the repair system	45
11.5	Repair system maintenance and remedial options	47
11.5.1	Overview	47
11.5.2	Substrate adjacent to the repair	48
11.5.3	Repairs to Type A defects	48
11.5.4	Repairs to Type B defects	48
11.5.5	Repair system	48
11.6	Repair lifetime considerations	49
11.6.1	Periodic review	49
11.6.2	Lifetime reduction	50
11.6.3	Lifetime extension	50
11.7	Future modifications	50
12	System testing	50
13	Decommissioning	51
Annex A (normative)	Design data sheet	52
Annex B (normative)	Qualification data	55
Annex C (normative)	Short-term pipe spool survival test	60
Annex D (normative)	Measurement of γ_{LCL} for through-wall defect calculation	62
Annex E (normative)	Measurement of performance test data	67
Annex F (normative)	Measurement of impact performance	69

Annex G (normative) Measurement of the degradation factor 70

Annex H (normative) Qualification of repair systems for other defects (with assessments based on substrate stress) 72

Annex I (Informative) Guidance on the selection of the appropriate defect size and geometry for through-wall defects (Type B defect) 75

Annex J (normative) Installer qualification 84

Annex K (informative) Installation requirements and guidance 87

Annex L (informative) Design considerations 89

Annex M (informative) Management of the integrity of composite repair systems to pipework and vessels 96

Bibliography 99