

DIN EN ISO 10424-2:2008-07 (E)

Petroleum and natural gas industries - Rotary drilling equipment - Part 2: Threading and gauging of rotary shouldered thread connections (ISO 10424-2:2007); English version EN ISO 10424-2:2007

Inhalt

Seite

Foreword	3
Introduction.....	4
1 Scope.....	5
2 Conformance — Units of measurement.....	5
3 Normative references.....	5
4 Terms, abbreviated terms, definitions and symbols	6
4.1 Terms and definitions	6
4.2 Design types and definitions	8
4.3 Abbreviations and symbols	9
5 Information to be supplied by purchaser.....	12
6 Threading	12
6.1 Thread profile and dimensions.....	12
6.2 Bevels for drill collars and tools that mate directly with drill collars	19
6.3 Low-torque feature	20
7 Product optional features	22
7.1 General	22
7.2 Stress-relief features.....	22
7.3 Benchmarks	25
7.4 Surface treatment	27
7.5 Cold working	27
7.6 Break-in	27
8 Product gauging	28
8.1 Gauging	28
8.2 Stand-off measurement	28
8.3 Gauge contact points.....	29
8.4 Lead measurement.....	29
8.5 Taper measurement	31
8.6 Thread height measurement and gauges	32
9 Gauge relationships for rotary shouldered connections	32
9.1 Gauge relationship	32
9.2 Gauge specifications	33
10 Gauge calibration	45
10.1 Calibration system	45
10.2 Acceptance criteria	45
10.3 Gauge measurement methods	45
10.4 Gauge certification	51
Annex A (informative) Tables in USC units	52
Annex B (informative) Care and use of regional master gauges	61
Annex C (normative) Shipment of reference master gauges	63
Annex D (normative) Care and use of working gauges	65
Annex E (informative) API gauge certification requirements	66

Annex F (informative) Other rotary shouldered connections	69
Annex G (informative) USC units conversion table	90
Annex H (informative) Recommended practice for gauging new rotary shouldered connections	91
Annex I (informative) Calculations	97
Annex J (informative) API grand and regional master rotary connection gauges	101