ISO 13704:2007-11 (E)

Petroleum, petrochemical and natural gas industries - Calculation of heater-tube thickness in petroleum refineries

Contents

Page

Foreword iv

1 Scope 1

2 Terms and definitions 1

3 General design information 3
3.1 Information required 3
3.2 Limitations for design procedures 4

4 Design 4
4.1 General 4
4.2 Equation for stress 7
4.3 Elastic design (lower temperatures) 7
4.4 Rupture design (higher temperatures) 8
4.5 Intermediate temperature range 8
4.6 Minimum allowable thickness 8
4.7 Minimum and average thicknesses 8
4.8 Equivalent tube metal temperature 9
4.9 Component fittings 13

5 Allowable stresses 15
5.1 General 15
5.2 Elastic allowable stress 16
5.3 Rupture allowable stress 16
5.4 Rupture exponent 16
5.5 Yield and tensile strengths 16
5.6 Larson-Miller parameter curves 16
5.7 Limiting design metal temperature 17
5.8 Allowable stress curves 17

6 Sample calculations 18
6.1 Elastic design 18
6.2 Thermal-stress check (for elastic range only) 19
6.3 Rupture design with constant temperature 23
6.4 Rupture design with linearly changing temperature 25

Annex A (informative) Estimation of remaining tube life 28

Annex B (informative) Calculation of maximum radiant section tube skin temperature 33

Annex C (normative) Thermal-stress limitations (elastic range) 44

Annex D (informative) Calculation sheets 48

Annex E (normative) Stress curves (SI units) 50

Annex F (normative) Stress curves (USC units) 70

Annex G (normative) Derivation of corrosion fraction and temperature fraction 90

Annex H (informative) Data sources 98

Bibliography 103