

DIN EN ISO 13503-2:2010-03 (E)

Petroleum and natural gas industries - Completion fluids and materials - Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations (ISO 13503-2:2006 + Amd 1:2009); English version EN ISO 13503-2:2006 + A1:2009

Inhalt	Seite
Foreword	4
A₁ Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Abbreviations	7
4 Standard proppant sampling procedure	7
4.1 General	7
4.2 Particle segregation	8
4.3 Equipment	8
4.4 Number of required samples — Bulk	11
4.4.1 Proppants for hydraulic fracturing	11
4.4.2 Gravel-packing media	11
4.5 Sampling — Bulk material	12
4.6 Sampling — Bagged material	12
4.6.1 Bags up to 50 kg (110 lb)	12
4.6.2 Totes/bulk bags/super sacks weighing up to 2 000 kg (4 400 lb)	12
5 Sample handling and storage	12
5.1 Sample reduction	12
5.2 Sample splitting	12
5.3 Sample and record retention and storage	12
6 Sieve analysis	13
6.1 Purpose	13
6.2 Description	13
6.3 Equipment and materials	13
6.4 Procedure	13
6.5 Calculation of the mean diameter, median diameter and standard deviation	14
6.5.1 General	14
6.5.2 Mean diameter	14
6.5.3 Median diameter	15
6.6 Sieve calibration	16
6.6.1 Purpose	16
6.6.2 Description	16
6.6.3 Procedure	17
6.6.4 Preparing calibration samples	18
7 Proppant sphericity and roundness	18
7.1 Purpose	18
7.2 Description	19
7.3 Apparatus capability	19
7.4 Procedure	19
7.5 Alternate method for determining average sphericity and roundness	20
7.5.1 Use of photomicrographs	20
7.5.2 Procedure	20

7.5.3	Suggested magnification for photomicrographs	20
8	Acid solubility	20
8.1	Purpose.....	20
8.2	Description	20
8.3	Equipment and materials	21
8.4	Procedure	21
8.4.1	General.....	21
8.4.2	Preparation of 12:3 HCl:HF solution	21
8.4.3	Solubility test	22
9	Turbidity test	22
9.1	Purpose.....	22
9.2	Description	23
9.3	Equipment and materials	23
9.4	Equipment calibration	23
9.5	Procedure	23
10	Procedures for determining proppant bulk density, apparent density and absolute density.....	24
10.1	Purpose.....	24
10.2	Description	24
10.3	Bulk density.....	24
10.3.1	Equipment and materials	24
10.3.2	Calibration of cylinder	25
10.3.3	Procedure	26
10.4	Apparent density.....	26
10.4.1	Equipment and materials	26
10.4.2	Procedure	27
10.5	Absolute density	28
10.5.1	Description	28
10.5.2	Equipment	28
10.5.3	Procedures	28
11	Proppant crush-resistance test.....	28
11.1	Purpose.....	28
11.2	Description	29
11.3	Equipment and materials	29
11.4	Sample preparation	29
11.5	Crush-resistance procedure.....	30
12	Loss on ignition of resin-coated proppant	32
12.1	Objective.....	32
12.2	Apparatus and materials.....	32
12.3	Loss-on-ignition procedure for whole-grain proppant	32
Annex A	(informative) Formazin solution preparation	34
A.1	Preparation of a formazin polymer solution for calibration	34
A.2	Equipment Calibration	34
Annex B	(informative) Proppant specifications	35
B.1	Fracturing proppant sizes.....	35
B.2	Gravel packing sizes	36
B.3	Sphericity and roundness.....	36
B.4	Acid solubility	37
B.5	Maximum proppant turbidity	37
B.6	Maximum crush material.....	37
B.6.1	General.....	37
B.6.2	Gravel packing proppants	37
B.6.3	Fracturing proppants	38
Bibliography	39