

# DIN EN ISO 10407-2:2010-08 (E)

Petroleum and natural gas industries - Rotary drilling equipment - Part 2:  
Inspection and classification of used drill stem elements (ISO 10407-2:2008 +  
Cor. 1:2009); English version EN ISO 10407-2:2008 + AC:2009, only on CD-ROM

---

## Contents

Page

Foreword.....	5
Introduction .....	6
1 Scope .....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 Symbols and abbreviated terms .....	14
4.1 Symbols .....	14
4.2 Abbreviated terms .....	15
5 Conformance.....	16
5.1 Basis for inspection .....	16
5.2 Repeatability of results .....	17
5.3 Ordering information .....	17
6 Quality assurance .....	17
6.1 General.....	17
6.2 Standardization and operating procedures .....	17
6.3 Equipment description .....	18
6.4 Personnel qualification .....	18
6.5 Dynamic test data demonstrating the system capabilities for detecting the reference indicators.....	18
6.6 Reports .....	18
7 Qualification of inspection personnel .....	18
7.1 General.....	18
7.2 Written procedure .....	18
7.3 Qualification responsibility and requirements .....	19
7.4 Training programmes .....	19
7.5 Examinations.....	19
7.6 Experience.....	19
7.7 Re-qualification .....	19
7.8 Documentation.....	20
7.9 NDT personnel certification.....	20
8 General inspection procedures.....	20
8.1 General.....	20
8.2 Owner/operator work site requirements for quality inspection.....	20
8.3 Documents at job site .....	20
8.4 Pre-inspection procedures .....	21
8.5 Drill-pipe and tool-joint classification markings .....	21
8.6 Post-inspection procedures .....	22
9 General non-destructive inspection method requirements .....	25
9.1 General.....	25
9.2 Equipment .....	25
9.3 Illumination.....	26
9.4 Magnetic-particle-inspection equipment.....	27
9.5 Ultrasonic .....	29
9.6 Electromagnetic inspection units .....	30
10 Drill stem element inspection and classification .....	30
10.1 Pipe body — Full-length visual inspection .....	30
10.2 Drill body — Outside diameter gauging .....	31
10.3 Pipe body — Ultrasonic wall-thickness gauging.....	33
10.4 Pipe body — Full-length electromagnetic inspection (EMI).....	35

10.5	Pipe body — Full-length ultrasonic transverse and wall thickness.....	37
10.6	Pipe body — Full-length ultrasonic transverse, wall thickness and longitudinal inspection .....	40
10.7	Drill-pipe body — External magnetic-particle inspection of the critical area .....	43
10.8	Drill-pipe body — Bi-directional external magnetic-particle inspection of the critical area.....	46
10.9	Pipe body — Full-length wall-loss inspection .....	49
10.10	Pipe body — Ultrasonic inspection of the critical area .....	51
10.11	Pipe body — Calculation of cross-sectional area .....	55
10.12	Pipe body — Document review (traceability) .....	56
10.13	Pipe body — Evaluation and classification .....	56
10.14	Tool joints .....	61
10.15	Tool joints — Check for box swell and pin stretch .....	66
10.16	Repair of rejected tool joints .....	67
10.17	Tool joints — Check tool-joint pin and box outside diameter and eccentric wear .....	67
10.18	Tool joints — Measure tool-joint pin and box outside diameter and check for eccentric wear.....	69
10.19	Tool joints — Check tool-joint pin and box tong space .....	70
10.20	Tool joints — Measure tool-joint pin and box tong space .....	71
10.21	Tool joint — Magnetic-particle inspection of the pin threads.....	72
10.22	Tool joint — Magnetic-particle inspection of box threads .....	74
10.23	Tool joints — Measure tool-joint pin inside diameter.....	76
10.24	Magnetic-particle inspection of the connection OD for heat-check cracking.....	77
10.25	Bi-directional wet magnetic-particle inspection of the connection OD for heat-check cracking .....	78
10.26	Tool joints — Measure the tool-joint counterbore depth, pin-base length and seal width .....	82
10.27	BHA connection — Visual inspection of bevels, seals, threads and stress-relief features .....	83
10.28	BHA — Measure box outside diameter, pin inside diameter, counterbore diameter and benchmark location if a benchmark is present.....	86
10.29	BHA — Check bevel diameter .....	88
10.30	BHA — Measure bevel diameter .....	89
10.31	BHA — Magnetic-particle inspection of the pin and box threads .....	89
10.32	BHA connection — Liquid-penetrant inspection of the pin and box threads .....	92
10.33	BHA — Dimensional measurement of stress-relief features .....	93
10.34	Length measurements of the counterbore, pin and pin neck.....	96
10.35	Drill collar — Visual full-length OD and ID, markings, fish-neck length and tong space .....	97
10.36	Drill-collar elevator groove and slip-recess magnetic-particle inspection .....	98
10.37	Drill-collar elevator-groove and slip-recess measurement.....	100
10.38	Subs (full-length visual OD and ID), fish-neck length, section-change radius and markings ..	102
10.39	Float-bore recess measurements .....	103
10.40	Magnetic-particle inspection of subs — Full-length, internal and external .....	105
10.41	HWDP — Visual full-length OD and ID, markings and tong space.....	107
10.42	Visual inspection and wear pattern report for kelly.....	108
10.43	Magnetic-particle evaluation of critical areas on kellys .....	110
10.44	Magnetic-particle evaluation, full length, of the drive section on kellys .....	110
10.45	Stabilizer (full-length visual OD and ID), fish-neck length, blade condition, ring gauge and markings.....	110
10.46	Magnetic-particle inspection of the base of stabilizer blades for cracking .....	112
10.47	Function test.....	114
10.48	Bi-directional, wet magnetic-particle inspection of the base of stabilizer blade for cracking .....	115
10.49	Visual inspection of jars (drilling and fishing), accelerators and shock subs .....	118
10.50	Maintenance review.....	119
10.51	Dimensional measurement of wear areas as specified by OEM requirements .....	119
10.52	Original equipment manufacturer designated testing for used equipment .....	120
10.53	MWD/LWD — Visual, full-length OD and ID, and markings, including visual inspection of hard-banding and coatings .....	120
10.54	Motors and turbines — Visual, full-length OD and ID and markings, including visual inspection of hard-banding and coatings.....	122

<b>10.55</b>	<b>Reamers, scrapers, and hole openers — Visual, full-length OD and ID and markings, including visual inspection of hard-banding and coatings.....</b>	<b>123</b>
<b>10.56</b>	<b>Rotary steerable — Visual, full-length OD and ID and markings, including visual inspection of hard-banding .....</b>	<b>124</b>
<b>10.57</b>	<b>Full-length drift.....</b>	<b>125</b>
<b>10.58</b>	<b>Proprietary equipment inspection .....</b>	<b>126</b>
<b>10.59</b>	<b>Hard-banding inspection .....</b>	<b>127</b>
<b>10.60</b>	<b>Transverse magnetic-particle inspection of tool-joint OD and ID under the pin threads .....</b>	<b>131</b>
<b>10.61</b>	<b>Drill-pipe body — Internal magnetic-particle inspection of the critical area .....</b>	<b>132</b>
<b>10.62</b>	<b>Drill-pipe body — Bi-directional, internal magnetic-particle inspection of the critical area .....</b>	<b>134</b>
<b>10.63</b>	<b>API external upset-thread connection inspection.....</b>	<b>136</b>
<b>Annex A</b>	<b>(normative) Original equipment manufacturer (OEM) requirements .....</b>	<b>138</b>
<b>Annex B</b>	<b>(normative) Required and additional inspections by product and class of service.....</b>	<b>140</b>
<b>Annex C</b>	<b>(normative) SI units .....</b>	<b>151</b>
<b>Annex D</b>	<b>(informative) USC units .....</b>	<b>180</b>
<b>Annex E</b>	<b>(informative) Inspection-level guidelines .....</b>	<b>209</b>
<b>Annex F</b>	<b>(informative) Proprietary drill stem connection .....</b>	<b>213</b>
<b>Annex G</b>	<b>(informative) Used work-string tubing proprietary-connection thread inspection.....</b>	<b>218</b>
<b>Bibliography</b>	<b>.....</b>	<b>220</b>