

# DIN EN ISO 28781:2010-12 (E)

Petroleum and natural gas industries –Drilling and production equipment –Subsurface barrier valves and related equipment (ISO 28781:2010);English version EN ISO 28781:2010

---

## Contents

Page

Foreword.....	4
Introduction .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	7
4 Abbreviated terms .....	12
5 Functional requirements .....	12
5.1 General.....	12
5.2 Functional characteristics .....	14
5.3 Well parameters .....	15
5.4 Operational parameters .....	15
5.5 Environmental compatibility.....	15
5.6 Compatibility with related well equipment.....	16
5.7 Optional requirements .....	16
6 Technical specification .....	16
6.1 General.....	16
6.2 Technical characteristics .....	17
6.3 Design criteria .....	17
6.4 Materials .....	18
6.5 Performance envelope .....	19
6.6 Design documentation .....	19
6.7 Design verification.....	20
6.8 Design validation .....	20
6.9 Design changes .....	20
6.10 Functional test .....	21
7 Supplier/manufacturer requirements.....	21
7.1 General.....	21
7.2 Documentation.....	21
7.3 Product identification .....	23
7.4 Quality requirements.....	23
7.5 Material documentation .....	25
7.6 Additional processes .....	25
7.7 Traceability .....	25
7.8 Quality controls.....	25
7.9 Shear device validation.....	28
7.10 Assembly and functional test.....	29
7.11 Manufacturing nonconformities.....	29
8 Handling, storage and preparation for transport .....	29
9 Repair/redress.....	30
Annex A (informative) Applications overview .....	31
Annex B (normative) Validation requirements for subsurface barrier valves .....	34
Annex C (normative) Functional testing .....	42
Annex D (normative) Validation requirements for subsurface-barrier-valve tools .....	44
Annex E (normative) Performance envelopes .....	46
Annex F (informative) Alternate barrier liquid leakage test acceptance criteria .....	48
Annex G (informative) Debris-settling design validation .....	49
Annex H (informative) Closure while flowing slurry test .....	51
Bibliography.....	52