

# ISO 10414-2:2011-06 (E)

## Petroleum and natural gas industries - Field testing of drilling fluids - Part 2: Oil-based fluids

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | v           |
| Introduction ..... |  | vi          |
| 1                  | Scope .....  | 1           |
| 2                  | Normative references .....   | 2           |
| 3                  | Terms and definitions .....  | 2           |
| 4                  | Symbols and abbreviated terms .....  | 3           |
| 4.1                | Symbols .....  | 3           |
| 4.2                | Abbreviated terms .....  | 9           |
| 5                  | Determination of drilling fluid density (mud weight) .....                                 | 10          |
| 5.1                | Principle .....  | 10          |
| 5.2                | Apparatus .....  | 10          |
| 5.3                | Procedure .....  | 10          |
| 5.4                | Calculation .....  | 10          |
| 6                  | Alternative method for determination of drilling fluid density .....                       | 12          |
| 6.1                | Principle .....  | 12          |
| 6.2                | Apparatus .....  | 12          |
| 6.3                | Procedure .....  | 13          |
| 6.4                | Calculation .....  | 14          |
| 7                  | Viscosity and gel strength .....   | 14          |
| 7.1                | Principle .....  | 14          |
| 7.2                | Determination of viscosity using the Marsh funnel .....                                    | 14          |
| 7.3                | Determination of viscosity and gel strength using a direct-reading viscometer .....        | 15          |
| 8                  | Static filtration .....  | 18          |
| 8.1                | Principle .....  | 18          |
| 8.2                | High-temperature/high-pressure test up to 175 °C (350 °F) .....                            | 18          |
| 8.3                | High-temperature/high-pressure test 175 °C (350 °F) up to and including 230 °C (450 °F) .. | 21          |
| 9                  | Retort test for oil, water and solids concentrations .....                                 | 23          |
| 9.1                | Principle .....  | 23          |
| 9.2                | Apparatus .....  | 24          |
| 9.3                | Procedure -- Volumetric method .....   | 25          |
| 9.4                | Calculation -- Volumetric method .....   | 26          |
| 9.5                | Procedure -- Gravimetric method .....  | 27          |
| 9.6                | Calculation -- Gravimetric method .....  | 29          |
| 9.7                | Calculation -- Volume fractions of oil, water and solids .....                             | 30          |
| 10                 | Chemical analysis of oil-based drilling fluids .....                                       | 32          |
| 10.1               | Principle .....  | 32          |
| 10.2               | Reagents and apparatus .....   | 33          |
| 10.3               | Base alkalinity demand, VB .....   | 34          |
| 10.4               | Whole-drilling-fluid alkalinity, VK .....  | 35          |
| 10.5               | Whole-drilling-fluid chloride concentration .....  | 37          |

|   |   |     |
|---|---|-----|
| 10.6  | Whole-drilling-fluid calcium concentration .....                              | 38  |
| 11  | Electrical stability test .....   | 39  |
| 11.1  | Principle .....   | 39  |
| 11.2  | Apparatus .....   | 39  |
| 11.3  | Equipment calibration/performance test .....                                  | 40  |
| 11.4  | Procedure .....   | 40  |
| 12  | Lime, salinity and solids calculations .....                                  | 41  |
| 12.1  | Principle .....   | 41  |
| 12.2  | Apparatus .....   | 42  |
| 12.3  | Whole-drilling-fluid calculations .....                                       | 42  |
| 12.4  | Aqueous phase calculations .....  | 44  |
| 12.5  | Soluble and insoluble whole-drilling-fluid sodium chloride calculations ..... | 48  |
| 12.6  | Calculation -- Solids in the whole drilling fluid .....                       | 49  |
| Annex A (informative) Measurement of shear strength using shearometer tube .....  |   | 54  |
| Annex B (informative) Determination of oil and water retained on cuttings .....   |   | 56  |
| Annex C (informative) Determination of aqueous-phase activity of emulsified water using an<br>electrohygrometer .....   |   | 61  |
| Annex D (informative) Determination of aniline point .....  |   | 64  |
| Annex E (informative) Lime, salinity and solids calculations .....  |   | 67  |
| Annex F (informative) Sampling, inspection and rejection of drilling materials .....  |   | 88  |
| Annex G (informative) Rig-site sampling .....   |   | 90  |
| Annex H (informative) Determination of cutting activity by the Chenevert method .....   |   | 93  |
| Annex I (informative) Chemical analysis of active sulfides by the Garrett gas train method .....  |   | 97  |
| Annex J (informative) Calibration and verification of glassware, thermometers, viscometers, retort<br>kit cup and drilling fluid balances .....   |   | 102 |
| Annex K (informative) High-temperature/high-pressure filtration testing of oil-based drilling fluids<br>using the permeability plugging apparatus and cells equipped with set-screw secured<br>end caps ..... |   | 107 |
| Annex L (informative) High-temperature/high-pressure filtration testing of oil-based drilling fluids<br>using the permeability plugging apparatus and cells equipped with threaded end caps .                 |   | 117 |
| Annex M (informative) Compatibility of elastomeric materials with non-aqueous-based drilling<br>fluids .....  |   | 127 |
| Annex N (informative) Sand content procedure for non-aqueous fluids .....   |   | 131 |
| Annex O (informative) Identification and monitoring of weight-material sag .....  |   | 132 |
| Annex P (informative) Oil-based drilling fluid report form .....  |   | 155 |
| Bibliography .....  |   | 156 |