

# DIN EN ISO 10414-2:2011-09 (E)

Petroleum and natural gas industries - Field testing of drillings fluids - Part 2: Oil-based fluids (ISO 10414-2:2011); English version EN ISO 10414-2:2011, only on CD-ROM

---

<b>Contents</b>		<b>Page</b>
Foreword .....		7
Introduction.....		8
<b>1</b>	<b>Scope .....</b>	<b>9</b>
<b>2</b>	<b>Normative references .....</b>	<b>10</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>10</b>
<b>4</b>	<b>Symbols and abbreviated terms .....</b>	<b>11</b>
<b>4.1</b>	<b>Symbols.....</b>	<b>11</b>
<b>4.2</b>	<b>Abbreviated terms .....</b>	<b>16</b>
<b>5</b>	<b>Determination of drilling fluid density (mud weight) .....</b>	<b>17</b>
<b>5.1</b>	<b>Principle .....</b>	<b>17</b>
<b>5.2</b>	<b>Apparatus.....</b>	<b>17</b>
<b>5.3</b>	<b>Procedure.....</b>	<b>18</b>
<b>5.4</b>	<b>Calculation .....</b>	<b>18</b>
<b>6</b>	<b>Alternative method for determination of drilling fluid density .....</b>	<b>20</b>
<b>6.1</b>	<b>Principle .....</b>	<b>20</b>
<b>6.2</b>	<b>Apparatus.....</b>	<b>20</b>
<b>6.3</b>	<b>Procedure.....</b>	<b>21</b>
<b>6.4</b>	<b>Calculation .....</b>	<b>22</b>
<b>7</b>	<b>Viscosity and gel strength.....</b>	<b>22</b>
<b>7.1</b>	<b>Principle .....</b>	<b>22</b>
<b>7.2</b>	<b>Determination of viscosity using the Marsh funnel.....</b>	<b>22</b>
<b>7.2.1</b>	<b>Apparatus.....</b>	<b>22</b>
<b>7.2.2</b>	<b>Procedure.....</b>	<b>22</b>
<b>7.3</b>	<b>Determination of viscosity and gel strength using a direct-reading viscometer .....</b>	<b>23</b>
<b>7.3.1</b>	<b>Apparatus.....</b>	<b>23</b>
<b>7.3.2</b>	<b>Procedure.....</b>	<b>24</b>
<b>7.3.3</b>	<b>Calculation .....</b>	<b>24</b>
<b>8</b>	<b>Static filtration .....</b>	<b>26</b>
<b>8.1</b>	<b>Principle .....</b>	<b>26</b>
<b>8.2</b>	<b>High-temperature/high-pressure test up to 175 °C (350 °F).....</b>	<b>26</b>
<b>8.2.1</b>	<b>Apparatus.....</b>	<b>26</b>
<b>8.2.2</b>	<b>Procedure.....</b>	<b>27</b>
<b>8.2.3</b>	<b>Calculation .....</b>	<b>29</b>
<b>8.3</b>	<b>High-temperature/high-pressure test 175 °C (350 °F) up to and including 230 °C (450 °F).....</b>	<b>29</b>
<b>8.3.1</b>	<b>Apparatus.....</b>	<b>29</b>
<b>8.3.2</b>	<b>Procedure.....</b>	<b>30</b>
<b>8.3.3</b>	<b>Calculation .....</b>	<b>31</b>
<b>9</b>	<b>Retort test for oil, water and solids concentrations .....</b>	<b>31</b>
<b>9.1</b>	<b>Principle .....</b>	<b>31</b>
<b>9.2</b>	<b>Apparatus.....</b>	<b>32</b>
<b>9.2.1</b>	<b>Retort instrument, as specified below.....</b>	<b>32</b>
<b>9.3</b>	<b>Procedure — Volumetric method .....</b>	<b>33</b>
<b>9.4</b>	<b>Calculation — Volumetric method.....</b>	<b>34</b>
<b>9.5</b>	<b>Procedure — Gravimetric method .....</b>	<b>35</b>

9.6	Calculation — Gravimetric method.....	38
9.7	Calculation — Volume fractions of oil, water and solids .....	39
10	Chemical analysis of oil-based drilling fluids.....	40
10.1	Principle.....	40
10.2	Reagents and apparatus .....	42
10.3	Base alkalinity demand, $V_B$ .....	42
10.3.1	Procedure .....	42
10.3.2	Calculation.....	43
10.4	Whole-drilling-fluid alkalinity, $V_K$ .....	43
10.4.1	Procedure .....	43
10.4.2	Calculation.....	44
10.5	Whole-drilling-fluid chloride concentration .....	45
10.5.1	Procedure .....	45
10.5.2	Calculation.....	46
10.6	Whole-drilling-fluid calcium concentration.....	46
10.6.1	Procedure .....	46
11	Electrical stability test.....	47
11.1	Principle.....	47
11.2	Apparatus .....	47
11.3	Equipment calibration/performance test.....	48
11.4	Procedure .....	48
12	Lime, salinity and solids calculations .....	49
12.1	Principle.....	49
12.2	Apparatus .....	50
12.3	Whole-drilling-fluid calculations .....	50
12.3.1	Whole-drilling-fluid lime concentration.....	50
12.3.2	Whole-drilling-fluid calcium chloride and sodium chloride concentrations .....	50
12.4	Aqueous phase calculations .....	52
12.5	Soluble and insoluble whole-drilling-fluid sodium chloride calculations .....	56
12.6	Calculation — Solids in the whole drilling fluid .....	57
12.6.1	Corrected solids concentration.....	57
12.6.2	Calculation — Oil-to-water ratio .....	58
12.6.3	Calculation — Oil-to-brine ratio.....	59
12.6.4	Calculation — Solids concentration and density.....	59
12.6.5	Calculation — Volume fraction and concentration of weighting material and low-gravity solids.....	60
Annex A	(informative) Measurement of shear strength using shearometer tube .....	62
A.1	Principle.....	62
A.2	Apparatus .....	62
A.3	Procedure .....	62
A.4	Calculation.....	63
Annex B	(informative) Determination of oil and water retained on cuttings.....	64
B.1	Principle.....	64
B.2	Apparatus .....	64
B.3	Procedure .....	65
B.4	Calculations.....	67
Annex C	(informative) Determination of aqueous-phase activity of emulsified water using an electrohygrometer .....	69
C.1	Principle.....	69
C.2	Reagents and apparatus .....	69
C.2.1	Standard saturated salt solutions.....	69
C.3	Procedure .....	70
C.3.1	Calibration of hygrometer.....	70
C.3.2	Measurement of oil-based drilling fluid activity, $a_{DF}$ .....	71
C.4	Calculation — Drilling fluid activity, $a_{DF}$ .....	71
Annex D	(informative) Determination of aniline point .....	72
D.1	Principle.....	72

D.2	Reagents and apparatus.....	72
D.3	Procedure.....	73
<b>Annex E</b>	<b>(informative) Lime, salinity and solids calculations .....</b>	<b>75</b>
E.1	Principle .....	75
E.2	Test data used in examples.....	75
E.3	Drilling fluid containing only CaCl <sub>2</sub> salt (drilling fluid A).....	76
E.4	Drilling fluid containing only NaCl salt (drilling fluid B).....	78
E.5	Drilling fluid containing both CaCl <sub>2</sub> and NaCl salts (drilling fluid C) .....	80
E.6	Drilling fluid containing both CaCl <sub>2</sub> and excess NaCl salts (drilling fluid D) .....	83
E.7	Calculation in spreadsheet — Drilling fluid A to drilling fluid D .....	86
<b>Annex F</b>	<b>(informative) Sampling, inspection and rejection of drilling materials .....</b>	<b>96</b>
F.1	Principle .....	96
F.2	Sampling of powdered material in packages .....	96
F.3	Sampling powdered material in bulk.....	96
F.4	Preparation of test sample .....	96
F.5	Test .....	97
F.6	Inspection.....	97
F.7	Rejection .....	97
F.8	Retesting .....	97
<b>Annex G</b>	<b>(informative) Rig-site sampling.....</b>	<b>98</b>
G.1	Principle .....	98
G.2	Bottom-flow sampling (preferred) .....	98
G.2.1	Apparatus.....	98
G.2.2	Procedure.....	98
G.3	Grab sampling .....	99
G.3.1	Apparatus.....	99
G.3.2	Procedure.....	99
<b>Annex H</b>	<b>(informative) Determination of cutting activity by the Chenevert method .....</b>	<b>101</b>
H.1	Principle .....	101
H.2	Reagents and apparatus.....	101
H.2.1	Standard saturated salt solutions .....	101
H.3	Procedure.....	102
H.3.1	Calibration of hygrometer .....	102
H.3.2	Measurement of oil-contaminated cuttings activity, $a_C$ .....	103
H.4	Calculation — Cuttings activity, $a_C$ .....	103
<b>Annex I</b>	<b>(informative) Chemical analysis of active sulfides by the Garrett gas train method.....</b>	<b>104</b>
I.1	Principle .....	104
I.2	Reagents and apparatus.....	104
I.3	Procedure.....	106
I.4	Calculation .....	108
<b>Annex J</b>	<b>(informative) Calibration and verification of glassware, thermometers, viscometers, retort kit cup and drilling fluid balances .....</b>	<b>109</b>
J.1	Principle .....	109
J.2	Calibration of apparatus .....	109
J.2.1	Volumetric glassware.....	109
J.2.2	Thermometers.....	109
J.2.3	Viscometers .....	109
J.2.4	Drilling fluid balances .....	109
J.2.5	Retort kit cups .....	109
J.3	Procedure — Calibration of graduated cylinders .....	110
J.4	Procedure — Calibration of thermometers.....	110
J.5	Procedure — Calibration of viscometers.....	112
J.6	Procedure — Calibration of retort kit cups.....	113
J.7	Procedure — Calibration of filter press gasket and O-rings.....	113

<b>Annex K (informative) High-temperature/high-pressure filtration testing of oil-based drilling fluids using the permeability plugging apparatus and cells equipped with set-screw secured end caps</b>	<b>114</b>
K.1 Principle	114
K.2 Safety considerations	114
K.3 Apparatus — Permeability plugging apparatus (PPA) with set-screw-secured end caps	116
K.4 Procedure for high-temperature, high-pressure (HTHP) filtration	118
K.4.1 Preheating the heating jacket	118
K.4.2 Loading the filtration cell	118
K.4.3 Pressurizing the cell	119
K.4.4 Conducting the filtration test	121
K.5 Test conclusion and disassembly	121
K.6 Calculation — Data reporting	123
K.6.1 Filtrate reporting	123
K.6.2 Spurt loss	123
K.6.3 Calculation	123
K.6.4 Filter cake reporting	123
<b>Annex L (informative) High-temperature/high-pressure filtration testing of oil-based drilling fluids using the permeability plugging apparatus and cells equipped with threaded end caps</b>	<b>124</b>
L.1 Principle	124
L.2 Safety considerations	124
L.3 Apparatus — Permeability plugging apparatus (PPA) with threaded end caps	126
L.4 Procedure for high-temperature, high-pressure (HTHP) filtration	128
L.4.1 Preheating the heating jacket	128
L.4.2 Loading the filtration cell	128
L.4.3 Pressurizing the cell	129
L.4.4 Conducting the filtration test	130
L.5 Test conclusion and disassembly	130
L.6 Calculating — Data reporting	132
L.6.1 Filtrate reporting	132
L.6.2 Spurt loss	132
L.6.3 Calculation	132
L.6.4 Filter cake reporting	132
<b>Annex M (informative) Compatibility of elastomeric materials with non-aqueous-based drilling fluids</b>	<b>133</b>
M.1 Principle	133
M.2 Apparatus and reagents	134
M.2.1 Standard reference elastomers	134
M.2.2 Standard reference test liquids	134
M.3 Procedure — Test specimen preparation	134
M.4 Procedure — Elastomer physical changes after immersion	134
M.4.1 Principle	134
M.4.2 Summary of immersion procedure	135
M.4.3 Summary of change in volume procedure	135
M.4.4 Summary of changes in tensile strength, elongation and hardness procedures	136
M.5 Procedure — Effect of immersion on a stressed elastomer specimen	136
<b>Annex N (informative) Sand content procedure for non-aqueous fluids</b>	<b>137</b>
N.1 Principle	137
N.2 Apparatus	137
N.3 Procedure	137
N.4 Calculation	137
<b>Annex O (informative) Identification and monitoring of weight-material sag</b>	<b>138</b>
O.1 Principle	138
O.2 Guidelines on using sag monitoring methods	138
O.3 Surface monitoring of weight-material sag	139
O.3.1 Principle	139
O.3.2 Apparatus	140
O.3.3 Procedure	140
O.3.4 Calculation	140

O.3.5	Data reporting .....	141
O.4	Field sag monitoring based on downhole density.....	143
O.4.1	Principle .....	143
O.4.2	Measurements of downhole pressure.....	143
O.4.3	Weight-material signatures using downhole pressure tools.....	144
O.4.4	Downhole pressure changes that are not caused by weight-material sag .....	146
O.4.5	Theoretical downhole density excluding effects in O.4.4 .....	149
O.4.6	Weight-material sag events caused by drillpipe rotation only .....	149
O.5	Dynamic weight-material sag test — VSST method .....	150
O.5.1	Principle .....	150
O.5.2	Apparatus .....	151
O.5.3	Procedure .....	152
O.5.4	Calculation .....	153
O.6	Rheological measurements of drilling fluids exhibiting weight-material sag.....	154
O.6.1	Principle .....	154
O.6.2	Scope .....	154
O.6.3	Apparatus .....	154
O.6.4	Sample preparation .....	155
O.6.5	Potential rheological tests.....	155
O.6.6	Data interpretation.....	156
O.7	Field sag monitoring based on critical wall shear stress .....	158
O.7.1	Principle .....	158
O.7.2	Predictive model.....	158
O.7.3	Comparison of laboratory and field data .....	160
O.8	Additional resource literature .....	160
<b>Annex P (informative) Oil-based drilling fluid report form .....</b>		<b>161</b>
<b>Bibliography.....</b>		<b>162</b>