

ISO 20312:2011-10 (E)

Petroleum and natural gas industries - Design and operating limits of drill strings with aluminium alloy components

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Symbols	3
3.3	Abbreviated terms	7
4	Properties of ADP and tool joints	8
4.1	General	8
4.2	New pipes and tool joints data	8
4.3	Buoyant weight	8
4.4	Mechanical properties	8
4.5	ADP with integral tool joint and heavy wall ADP	11
5	Considerations and limitations of drill string design using ADP	15
5.1	Application aspects of aluminium alloy drill pipe	15
5.2	General principles of aluminium drill string assembly design	16
5.3	Influence of temperature on choice of material for drill pipe	17
5.4	Resistance to hydroabrasive and corrosive damage	23
5.5	Buckling	24
6	Basic requirements for calculation of drill strings containing ADP	26
7	Drill pipe operation	27
7.1	Operations management	27
7.2	General drill pipe operating recommendations	27
7.3	Fatigue strength limitations	31
7.4	Combined load capacity limitation	32
8	Wear-based inspection, identification and classification of aluminium drill pipe	36
8.1	Inspection	36
8.2	Wear-based marking and identification of pipe and tool joints	38
8.3	Wear-based pipe classification	39
8.4	Wear-based tool joints classification	40
8.5	Pipe repairing and discarding	40
9	Transportation and storage of pipe	41
9.1	Transportation of pipe	41
9.2	Storage of pipe	41
Annex A (informative)	Drill pipe design, range and technical properties of integral tool joint ADP and heavy wall ADP	42
Annex B (normative)	Calculations	47

Annex C (informative) Conversion of SI units to USC units	58
Bibliography	59