

# ISO 12212:2012-08 (E)

## Petroleum, petrochemical and natural gas industries - Hairpin-type heat exchangers

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative reference .....	1
3	Terms and definitions .....	1
4	General .....	3
5	Proposal information required .....	4
6	Drawings and other required data .....	4
6.1	Outline drawings and other supporting data .....	4
6.2	Information required after outline drawings are reviewed .....	5
6.3	Reports and records .....	6
7	Design .....	7
7.1	Design temperature .....	7
7.2	Design pressure .....	7
7.3	Cyclic design .....	7
7.4	Shell .....	8
7.5	Front closure .....	8
7.6	Rear closure .....	10
7.7	Tube bundle .....	11
7.8	Nozzles and other connections .....	14
7.9	Shell supports .....	18
7.10	Gaskets .....	19
7.11	Flanged external girth joints .....	19
7.12	Cladding for corrosion allowance .....	19
8	Materials .....	20
8.1	General .....	20
8.2	Requirements for carbon steel in sour or wet hydrogen sulfide service .....	20
8.3	Gaskets .....	20
8.4	Tubes .....	20
9	Fabrication .....	21
9.1	Shells .....	21
9.2	Tubes .....	21
9.3	Welding .....	21
9.4	Heat treatment .....	22
9.5	Dimensional tolerances .....	22
9.6	Gasket contact surfaces other than nozzle flange facings .....	23
9.7	Tube-to-tubesheet joints .....	23
9.8	Assembly .....	24
10	Inspection and testing .....	24
10.1	Quality assurance .....	24
10.2	Quality control .....	24

10.3	Pressure testing .....	26
10.4	Nameplates and stampings .....	26
11	Preparation for shipment .....	27
11.1	Protection .....	27
11.2	Identification .....	27
12	Supplemental requirements .....	28
12.1	General .....	28
12.2	Design .....	28
12.3	Examination .....	28
Annex A (informative) Recommended practices .....		30
Annex B (informative) Hairpin heat exchanger checklist .....		32
Annex C (informative) Hairpin heat exchanger data sheets .....		34
Bibliography .....		45