

# ISO 12212:2012-08 (E)

## Petroleum, petrochemical and natural gas industries - Hairpin-type heat exchangers

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | v           |
| Introduction ..... |   | vi          |
| 1                  | Scope .....   | 1           |
| 2                  | Normative reference .....   | 1           |
| 3                  | Terms and definitions .....   | 1           |
| 4                  | General .....   | 3           |
| 5                  | Proposal information required .....   | 4           |
| 6                  | Drawings and other required data .....                                      | 4           |
| 6.1                | Outline drawings and other supporting data .....                            | 4           |
| 6.2                | Information required after outline drawings are reviewed .....              | 5           |
| 6.3                | Reports and records .....   | 6           |
| 7                  | Design .....  | 7           |
| 7.1                | Design temperature .....  | 7           |
| 7.2                | Design pressure .....   | 7           |
| 7.3                | Cyclic design .....   | 7           |
| 7.4                | Shell .....   | 8           |
| 7.5                | Front closure .....   | 8           |
| 7.6                | Rear closure .....  | 10          |
| 7.7                | Tube bundle .....   | 11          |
| 7.8                | Nozzles and other connections .....   | 14          |
| 7.9                | Shell supports .....  | 18          |
| 7.10               | Gaskets .....   | 19          |
| 7.11               | Flanged external girth joints .....   | 19          |
| 7.12               | Cladding for corrosion allowance .....                                      | 19          |
| 8                  | Materials .....   | 20          |
| 8.1                | General .....   | 20          |
| 8.2                | Requirements for carbon steel in sour or wet hydrogen sulfide service ..... | 20          |
| 8.3                | Gaskets .....   | 20          |
| 8.4                | Tubes .....   | 20          |
| 9                  | Fabrication .....   | 21          |
| 9.1                | Shells .....  | 21          |
| 9.2                | Tubes .....   | 21          |
| 9.3                | Welding .....   | 21          |
| 9.4                | Heat treatment .....  | 22          |
| 9.5                | Dimensional tolerances .....  | 22          |
| 9.6                | Gasket contact surfaces other than nozzle flange facings .....              | 23          |
| 9.7                | Tube-to-tubesheet joints .....  | 23          |
| 9.8                | Assembly .....  | 24          |
| 10                 | Inspection and testing .....  | 24          |
| 10.1               | Quality assurance .....   | 24          |
| 10.2               | Quality control .....   | 24          |

|  |                                 |    |
|--|---------------------------------|----|
| 10.3   | Pressure testing .....          | 26 |
| 10.4   | Nameplates and stampings .....  | 26 |
| 11   | Preparation for shipment .....  | 27 |
| 11.1   | Protection .....                | 27 |
| 11.2   | Identification .....            | 27 |
| 12   | Supplemental requirements ..... | 28 |
| 12.1   | General .....                   | 28 |
| 12.2   | Design .....                    | 28 |
| 12.3   | Examination .....               | 28 |
| Annex A (informative) Recommended practices .....              |                                 | 30 |
| Annex B (informative) Hairpin heat exchanger checklist .....   |                                 | 32 |
| Annex C (informative) Hairpin heat exchanger data sheets ..... |                                 | 34 |
| Bibliography .....   |                                 | 45 |