

DIN EN ISO 15156-2:2015-12 (E)

Petroleum and natural gas industries - Materials for use in H₂S-containing environments in oil and gas production - Part 2: Cracking-resistant carbon and low-alloy steels, and the use of cast irons (ISO 15156-2:2015)

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	7
3 Terms and definitions	8
4 Symbols and abbreviated terms	11
5 Purchasing information	11
6 Factors affecting the behaviour of carbon and low alloy steels in H₂S-containing environments	12
7 Qualification and selection of carbon and low-alloy steels with resistance to SSC, SOHIC and SZC	13
7.1 Option 1 — Selection of SSC-resistant steels (and cast irons) using A.2.....	13
7.1.1 For $p_{\text{H}_2\text{S}} < 0,3$ kPa (0,05 psi).....	13
7.1.2 For $p_{\text{H}_2\text{S}} \geq 0,3$ kPa (0,05 psi).....	13
7.2 Option 2 — Selection of steels for specific sour-service applications or for ranges of sour service.....	13
7.2.1 Sulfide stress-cracking.....	13
7.2.2 SOHIC and SZC.....	15
7.3 Hardness requirements.....	15
7.3.1 General.....	15
7.3.2 Parent metals.....	15
7.3.3 Welds.....	15
7.4 Other fabrication methods.....	21
8 Evaluation of carbon and low alloy steels for their resistance to HIC/SWC	21
9 Marking, labelling, and documentation	22
Annex A (normative) SSC-resistant carbon and low alloy steels (and requirements and recommendations for the use of cast irons)	23
Annex B (normative) Qualification of carbon and low-alloy steels for H₂S service by laboratory testing	32
Annex C (informative) Determination of H₂S partial pressure	40
Annex D (informative) Recommendations for determining pH	42
Annex E (informative) Information that should be supplied for material purchasing	47
Bibliography	49