

ISO 24817:2017-08 (E)

Petroleum, petrochemical and natural gas industries - Composite repairs for pipework - Qualification and design, installation, testing and inspection

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and abbreviated terms | 6 |
| 4.1 | Symbols | 6 |
| 4.2 | Abbreviated terms | 9 |
| 5 | Applications | 9 |
| 6 | Summary of key issues | 11 |
| 7 | Qualification and design | 13 |
| 7.1 | Repair feasibility assessment | 13 |
| 7.2 | Repair class | 14 |
| 7.3 | Repair design lifetime | 14 |
| 7.4 | Required data | 15 |
| 7.4.1 | Background | 15 |
| 7.4.2 | Original equipment design data | 15 |
| 7.4.3 | Maintenance and operational histories | 15 |
| 7.4.4 | Service condition data | 15 |
| 7.4.5 | Repair system qualification data | 16 |
| 7.5 | Design methodology | 17 |
| 7.5.1 | Overview | 17 |
| 7.5.2 | Environmental compatibility | 19 |
| 7.5.3 | Design temperature effects | 19 |
| 7.5.4 | Design based on substrate load sharing (defect type A) | 21 |
| 7.5.5 | Design based on repair laminate allowable strains (defect type A) | 23 |
| 7.5.6 | Design based on repair-allowable stresses determined by performance testing (defect type A) | 24 |
| 7.5.7 | Design of repairs for through-wall defects (defect type B) | 25 |
| 7.5.8 | Axial extent of repair | 28 |
| 7.5.9 | Optional design considerations | 30 |
| 7.5.10 | Dent and/or gouge type defects | 34 |
| 7.5.11 | Fretting type defects | 34 |
| 7.5.12 | Delamination or blister type defects | 34 |
| 7.5.13 | Repair of other components | 35 |
| 7.5.14 | Design output | 38 |
| 7.6 | Re-qualification of the repair system | 38 |
| 7.6.1 | Overview | 38 |
| 7.6.2 | For type A defect repairs | 38 |
| 7.6.3 | For type B defect repairs | 38 |
| 8 | Installation | 39 |
| 8.1 | Storage conditions | 39 |

| | | |
|-------|---|----|
| 8.2 | Documentation prior to repair application | 39 |
| 8.2.1 | Method statement | 39 |
| 8.2.2 | Work pack | 39 |
| 8.3 | Installer qualifications | 40 |
| 8.4 | Installation procedure | 40 |
| 8.5 | Repair completion documentation | 41 |
| 8.6 | Live repairs | 43 |
| 8.7 | Repair of clamps, piping components, tanks, or vessels | 43 |
| 8.8 | Environmental considerations | 43 |
| 9 | Testing and inspection | 43 |
| 9.1 | General | 43 |
| 9.2 | Allowable defects for the repair system | 44 |
| 9.3 | Repair of defects within the repair system | 47 |
| 9.4 | Inspection methods | 48 |
| 9.5 | Repair system maintenance and remedial options | 48 |
| 9.5.1 | Overview | 48 |
| 9.5.2 | Condition of the repair - visual inspection | 48 |
| 9.5.3 | Condition of the pipe substrate | 49 |
| 9.5.4 | Remedial options | 49 |
| 9.5.5 | Extension (revalidation) of repair design lifetime | 49 |
| 9.5.6 | Future modifications | 50 |
| 10 | System testing | 50 |
| 11 | Decommissioning | 51 |
| | Annex A (normative) Design data sheet | 52 |
| | Annex B (normative) Qualification data | 55 |
| | Annex C (normative) Short-term pipe spool survival test | 59 |
| | Annex D (normative) Measurement of LCL for through-wall defect calculation | 61 |
| | Annex E (normative) Measurement of performance test data | 64 |
| | Annex F (normative) Measurement of impact performance | 67 |
| | Annex G (normative) Measurement of the degradation factor | 68 |
| | Annex H (informative) Axial extent of repair look-up table | 70 |
| | Annex I (normative) Installer qualification | 72 |
| | Annex J (informative) Installation requirements and guidance | 75 |
| | Annex K (informative) Design considerations | 77 |
| | Annex L (informative) Management of the integrity of composite repair systems to pipework and vessels | 82 |
| | Bibliography | 86 |