

DIN EN ISO 11961:2019-08 (E)

Petroleum and natural gas industries - Steel drill pipe (ISO 11961:2018); English version EN ISO 11961:2018, only on CD-ROM

| Contents | | Page |
|---|--|-------------|
| Foreword | | viii |
| Introduction | | ix |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms, definitions, symbols and abbreviated terms | | 2 |
| 3.1 Terms and definitions..... | | 2 |
| 3.2 Symbols and abbreviated terms..... | | 7 |
| 4 Conformance | | 9 |
| 4.1 Dual citing of normative references..... | | 9 |
| 4.2 Units of measurement..... | | 9 |
| 5 Information to be supplied when placing orders for drill-pipe | | 9 |
| 5.1 Grades D95 and F105..... | | 9 |
| 5.2 General information..... | | 10 |
| 5.3 Additional information..... | | 10 |
| 6 Requirements for drill-pipe | | 11 |
| 6.1 General..... | | 11 |
| 6.2 Dimensions, masses and connections..... | | 11 |
| 6.2.1 Standard configuration..... | | 11 |
| 6.2.2 Alternative configurations..... | | 12 |
| 6.2.3 Drill-pipe weld neck diameters..... | | 12 |
| 6.2.4 Tool-joint inside diameters..... | | 12 |
| 6.2.5 Length..... | | 12 |
| 6.2.6 Length of tool-joint outside diameter..... | | 12 |
| 6.2.7 End-drift..... | | 12 |
| 6.2.8 Drill-pipe body and tool-joint alignment..... | | 12 |
| 6.2.9 Weld-zone profile..... | | 13 |
| 6.3 Material requirements..... | | 13 |
| 6.3.1 General..... | | 13 |
| 6.3.2 Weld-zone yield strength..... | | 13 |
| 6.3.3 Weld-zone hardness..... | | 13 |
| 6.3.4 Weld-zone Charpy V-notch absorbed-energy requirements..... | | 14 |
| 6.3.5 Weld-zone Charpy V-notch absorbed energy — Alternative requirements..... | | 14 |
| 6.3.6 Weld-zone transverse side bend properties..... | | 14 |
| 6.3.7 Sulfide stress cracking test — Grades D and F..... | | 14 |
| 6.4 Process of manufacture for drill-pipe..... | | 15 |
| 6.4.1 Processes requiring validation..... | | 15 |
| 6.4.2 Welding qualification..... | | 15 |
| 6.4.3 Welding of tool joints to drill-pipe body and post-weld heat treatment..... | | 15 |
| 6.4.4 Weld machining..... | | 15 |
| 6.4.5 Internal coating..... | | 15 |
| 6.4.6 External coating..... | | 15 |
| 6.4.7 Thread protection..... | | 16 |
| 6.5 Traceability..... | | 16 |
| 6.6 Testing — General..... | | 16 |
| 6.6.1 Test equipment calibration..... | | 16 |
| 6.6.2 Dimensional inspection..... | | 16 |

| | | |
|--------|--|----|
| 6.6.3 | Drill-pipe length | 16 |
| 6.6.4 | Straightness | 16 |
| 6.6.5 | End-drift test | 16 |
| 6.6.6 | Internal profile | 17 |
| 6.6.7 | Drill-pipe body and tool-joint alignment | 17 |
| | Testing of welds | 17 |
| 6.7.1 | Lot size | 17 |
| 6.7.2 | Test specimens | 17 |
| 6.8 | Tensile test | 17 |
| 6.8.1 | Procedures | 17 |
| 6.8.2 | Test equipment calibration | 17 |
| 6.8.3 | Specimens | 17 |
| 6.8.4 | Frequency | 18 |
| 6.8.5 | Defective specimen | 18 |
| 6.8.6 | Re-tests | 18 |
| 6.9 | Hardness test | 18 |
| 6.9.1 | Procedures | 18 |
| 6.9.2 | Surface hardness test | 18 |
| 6.9.3 | Surface hardness — Re-test | 18 |
| 6.9.4 | Through-wall hardness test | 19 |
| 6.9.5 | Through-wall hardness — Re-tests | 19 |
| 6.10 | Charpy V-notch impact test | 19 |
| 6.10.1 | Procedures | 19 |
| 6.10.2 | Specimen size and orientation | 19 |
| 6.10.3 | Test frequency | 19 |
| 6.10.4 | Re-tests | 19 |
| 6.10.5 | Defective specimens | 20 |
| 6.11 | Transverse side-bend test | 20 |
| 6.11.1 | Procedure | 20 |
| 6.11.2 | Specimens | 20 |
| 6.11.3 | Test frequency | 20 |
| 6.11.4 | Re-tests | 20 |
| 6.12 | Imperfections and defects in drill-pipe | 20 |
| 6.12.1 | General | 20 |
| 6.12.2 | Weld zone defects | 21 |
| 6.12.3 | Process control plan | 21 |
| 6.13 | Visual inspection of the drill-pipe weld zone | 21 |
| 6.13.1 | General | 21 |
| 6.13.2 | Disposition of defects | 21 |
| 6.14 | Non-destructive examination of the weld zone | 21 |
| 6.14.1 | General | 21 |
| 6.14.2 | Wet fluorescent magnetic-particle inspection | 21 |
| 6.14.3 | Ultrasonic inspection — Procedure | 22 |
| 6.14.4 | Ultrasonic inspection — Reference standard | 22 |
| 6.14.5 | Ultrasonic inspection — System capability records | 22 |
| 6.14.6 | Disposition of defects | 23 |
| 6.15 | Marking of drill-pipe | 23 |
| 6.15.1 | General | 23 |
| 6.15.2 | Drill-pipe marking | 23 |
| 6.15.3 | Traceability marking | 23 |
| 6.15.4 | Drill-pipe marking on the pipe body | 23 |
| 6.15.5 | Drill-pipe marking on the tool joint | 24 |
| 6.16 | Minimum facility requirements for drill-pipe manufacturers | 24 |
| 6.17 | Documentation requirements of drill-pipe | 24 |
| 6.17.1 | Standard documentation | 24 |
| 6.17.2 | Supplementary documents | 25 |
| 6.17.3 | Electronic data interchange | 25 |
| 6.17.4 | Retention of records | 25 |

| | | |
|----------|---|-----------|
| 7 | Requirements for drill-pipe body | 25 |
| 7.1 | Information to be supplied when placing orders for drill-pipe bodies | 25 |
| 7.2 | Dimensional and mass requirements | 26 |
| | 7.2.1 General | 26 |
| | 7.2.2 Configuration | 26 |
| | 7.2.3 Internal upset area | 26 |
| | 7.2.4 Outside-diameter tolerance | 26 |
| | 7.2.5 Inside diameter | 26 |
| | 7.2.6 Pipe-body wall thickness and tolerance | 27 |
| | 7.2.7 Length | 27 |
| | 7.2.8 Mass | 27 |
| | 7.2.9 Straightness | 27 |
| | 7.2.10 Upset and drill-pipe body alignment | 27 |
| | 7.2.11 Upset ovality | 28 |
| 7.3 | Material requirements | 28 |
| | 7.3.1 Chemical composition | 28 |
| | 7.3.2 Tensile requirements | 28 |
| | 7.3.3 Charpy V-notch absorbed-energy requirements — Grade E | 28 |
| | 7.3.4 Charpy V-notch absorbed-energy requirements — Grades X, G, S, D and F | 28 |
| | 7.3.5 Charpy V-notch absorbed-energy requirements — Alternative temperature | 29 |
| | 7.3.6 Surface hardness requirements | 29 |
| 7.4 | Process of manufacture | 29 |
| | 7.4.1 Processes requiring validation | 29 |
| | 7.4.2 General | 29 |
| | 7.4.3 Heat treatment | 29 |
| | 7.4.4 External coating | 29 |
| 7.5 | Traceability | 29 |
| 7.6 | Testing — General | 30 |
| | 7.6.1 Test-equipment calibration | 30 |
| | 7.6.2 Heat-treatment lot | 30 |
| 7.7 | Testing of chemical composition | 30 |
| | 7.7.1 Heat analysis | 30 |
| | 7.7.2 Product analysis | 30 |
| | 7.7.3 Test method | 30 |
| | 7.7.4 Re-test of product analysis | 30 |
| 7.8 | Tensile tests | 31 |
| | 7.8.1 Procedures | 31 |
| | 7.8.2 Test equipment calibration | 31 |
| | 7.8.3 Test specimens | 31 |
| | 7.8.4 Frequency of testing | 31 |
| | 7.8.5 Heat control test | 31 |
| | 7.8.6 Re-tests | 31 |
| | 7.8.7 Defective specimens | 32 |
| 7.9 | Charpy V-notch impact tests | 32 |
| | 7.9.1 Procedure | 32 |
| | 7.9.2 Specimen size and location | 32 |
| | 7.9.3 Frequency of testing | 32 |
| | 7.9.4 Heat control test | 32 |
| | 7.9.5 Re-test | 32 |
| | 7.9.6 Defective specimens | 33 |
| 7.10 | Drill-pipe-body wall thickness | 33 |
| 7.11 | Drill-pipe-body length | 33 |
| 7.12 | Internal upset | 33 |
| 7.13 | Internal profile | 33 |
| 7.14 | Straightness | 34 |
| 7.15 | Upset and drill-pipe body alignment | 34 |
| 7.16 | Mass determination | 34 |

| | | |
|------|---|-----------|
| 7.17 | Imperfections and defects of drill-pipe body..... | 34 |
| | 7.17.1 General..... | 34 |
| | 7.17.2 Surface-breaking pipe-body defects..... | 34 |
| | 7.17.3 Surface-breaking upset defects..... | 35 |
| | 7.17.4 Elephant hide..... | 35 |
| | 7.17.5 Quench cracks..... | 35 |
| | 7.17.6 Process control plan..... | 35 |
| 7.18 | Visual inspection of drill-pipe body..... | 35 |
| | 7.18.1 General..... | 35 |
| | 7.18.2 Coverage..... | 35 |
| | 7.18.3 Disposition..... | 35 |
| | 7.18.4 Elephant hide..... | 35 |
| 7.19 | Non-destructive examination..... | 36 |
| | 7.19.1 General..... | 36 |
| | 7.19.2 Coverage..... | 36 |
| | 7.19.3 Applicable standards..... | 36 |
| | 7.19.4 Reference standards..... | 37 |
| | 7.19.5 Documented procedures..... | 37 |
| | 7.19.6 Inspection thresholds..... | 37 |
| | 7.19.7 Automated inspection-system signal evaluation..... | 37 |
| | 7.19.8 NDE system capability records..... | 37 |
| | 7.19.9 Evaluation of indications (prove-up)..... | 38 |
| | 7.19.10 Disposition of defects..... | 38 |
| 7.20 | Marking..... | 39 |
| | 7.20.1 General..... | 39 |
| | 7.20.2 Paint-stencilled marking sequence..... | 39 |
| 7.21 | Minimum facility requirements for drill-pipe-body manufacturer..... | 40 |
| 7.22 | Documentation requirements..... | 40 |
| | 7.22.1 Certificate of inspection..... | 40 |
| | 7.22.2 Tally list..... | 41 |
| | 7.22.3 Electronic data interchange..... | 41 |
| | 7.22.4 Retention of records..... | 41 |
| | Requirements for tool joints..... | 41 |
| 8.1 | Information to be supplied when placing orders for tool joints..... | 41 |
| 8.2 | Dimensional requirements..... | 42 |
| | 8.2.1 General..... | 42 |
| | 8.2.2 Configuration..... | 42 |
| | 8.2.3 Tool-joint type..... | 42 |
| | 8.2.4 Dimensions..... | 42 |
| | 8.2.5 Rotary shouldered connection..... | 42 |
| 8.3 | Material requirements..... | 42 |
| | 8.3.1 Chemical composition..... | 42 |
| | 8.3.2 Tensile requirements..... | 42 |
| | 8.3.3 Hardness..... | 43 |
| | 8.3.4 Charpy V-notch absorbed energy requirements..... | 43 |
| 8.4 | Process of manufacture..... | 43 |
| | 8.4.1 Processes requiring validation..... | 43 |
| | 8.4.2 Material..... | 43 |
| | 8.4.3 Heat treatment..... | 43 |
| | 8.4.4 Threading..... | 43 |
| | 8.4.5 Surface treatment to minimize galling..... | 44 |
| | 8.4.6 Break-in procedure..... | 44 |
| | 8.4.7 Hard banding..... | 44 |
| | 8.4.8 Thread protection..... | 44 |
| 8.5 | Traceability..... | 44 |
| 8.6 | Testing — General..... | 44 |
| | 8.6.1 Test-equipment calibration..... | 44 |
| | 8.6.2 Heat-treatment lot..... | 44 |

| | | |
|--|--|------------|
| 8.7 | Testing of chemical composition | 44 |
| 8.7.1 | General..... | 44 |
| 8.7.2 | Product analyses | 45 |
| 8.7.3 | Test method..... | 45 |
| 8.8 | Tensile tests | 45 |
| 8.8.1 | Procedures | 45 |
| 8.8.2 | Test-equipment calibration | 45 |
| 8.8.3 | Test specimens..... | 45 |
| 8.8.4 | Frequency of test..... | 45 |
| 8.8.5 | Heat control tensile tests | 45 |
| 8.8.6 | Re-test..... | 46 |
| 8.8.7 | Defective specimens..... | 46 |
| 8.9 | Hardness tests | 46 |
| 8.9.1 | Procedure..... | 46 |
| 8.9.2 | Test specimen | 46 |
| 8.9.3 | Frequency of testing | 46 |
| 8.9.4 | Heat control hardness tests..... | 46 |
| 8.9.5 | Re-tests..... | 46 |
| 8.10 | Charpy V-notch impact tests | 47 |
| 8.10.1 | Procedures..... | 47 |
| 8.10.2 | Specimen size and location..... | 47 |
| 8.10.3 | Frequency of testing | 47 |
| 8.10.4 | Heat control test..... | 47 |
| 8.10.5 | Re-test..... | 47 |
| 8.10.6 | Defective specimens..... | 48 |
| 8.11 | Imperfections and defects..... | 48 |
| 8.11.1 | General..... | 48 |
| 8.11.2 | Surface breaking defects | 48 |
| 8.11.3 | Quench cracks | 48 |
| 8.11.4 | Process control plan..... | 48 |
| 8.12 | Non-destructive examination..... | 48 |
| 8.12.1 | General..... | 48 |
| 8.12.2 | Wet magnetic-particle inspection..... | 48 |
| 8.12.3 | Disposition of defects..... | 49 |
| 8.13 | Marking..... | 49 |
| 8.13.1 | General..... | 49 |
| 8.13.2 | Die stamp marking..... | 49 |
| 8.14 | Minimum facility requirements for tool-joint manufacturers | 49 |
| 8.15 | Documentation requirements for tool joints | 50 |
| 8.15.1 | Certificate of inspection..... | 50 |
| 8.15.2 | Electronic data interchange | 50 |
| 8.15.3 | Retention of records | 51 |
| Annex A (normative) Tables in SI units | | 52 |
| Annex B (normative) Figures in SI (USC) units | | 69 |
| Annex C (normative) Tables in USC units | | 81 |
| Annex D (normative) Purchaser inspection | | 98 |
| Annex E (informative) Supplementary requirements | | 99 |
| Annex F (informative) Procedures used to convert from USC units to SI units for drill-pipe..... | | 102 |
| Annex G (normative) Product specification levels | | 106 |
| Bibliography | | 108 |