

DIN EN ISO 21857:2022-08 (E)

Petroleum, petrochemical and natural gas industries - Prevention of corrosion on pipeline systems influenced by stray currents (ISO 21857:2021)

Contents		Page
European foreword		4
Foreword		5
Introduction		6
1 Scope		7
2 Normative references		7
3 Terms and definitions		8
4 Abbreviations and symbols		9
4.1 Abbreviations		9
4.2 Symbols		10
5 Information exchange and co-operation		11
6 Common sources of interference that can affect corrosion		12
6.1 General		12
6.2 Direct current		13
6.2.1 General		13
6.2.2 Traction systems		13
6.2.3 Industrial systems		13
6.3 Alternating current		13
6.3.1 General		13
6.3.2 Overhead and buried power lines		14
6.4 High-voltage direct current transmission systems		14
6.5 Natural interference		14
6.5.1 General		14
6.5.2 Geomagnetic (telluric) interference		14
6.5.3 Tidal interference effects		15
7 Identification and measurement of stray current interference		15
7.1 Principle		15
7.2 Stray Current interference		16
7.2.1 Inductive and conductive coupling from remote sources		16
7.2.2 Conductive coupling from nearby sources		16
7.3 Measurement of electrical parameters		16
7.3.1 Data acquisition systems		16
7.3.2 Possible errors in AC measurements		17
7.3.3 Potential measurement		17
7.3.4 Current measurement on probes		17
7.3.5 IR-free potential measurement on coupons or probes		17
7.3.6 Duration of the measurement		17
7.3.7 Specific requirements for coupons or probes		18
7.4 Corrosion rate measurement		18
8 Acceptance criteria for DC interference		18
8.1 Overview of criteria		18
8.2 Corrosion rate		19

8.3	Criteria for steel and cast iron	20
8.3.1	Time constant interference	20
8.3.2	Time variant interference	21
8.4	Criteria for steel pipes in concrete based on potential measurements without cathodic protection	22
8.4.1	Time constant anodic interference	22
8.4.2	Time variant interference	22
9	Reduction of DC stray current interference	22
9.1	General	22
9.2	Modifications to the source of interference	23
9.2.1	Principles	23
9.2.2	Direct current systems at industrial sites	23
9.2.3	Direct current systems at ports	23
9.2.4	Direct current traction systems	23
9.2.5	Cathodic protection systems	24
9.2.6	Telluric interference	25
9.2.7	Direct current communication systems	25
10	Modifications to the interfered structure	25
10.1	General	25
10.2	Design prerequisites	26
10.2.1	Coatings	26
10.2.2	Isolation from other structures	26
10.2.3	Distance to be maximized	26
10.2.4	Installation of mitigation devices	26
10.2.5	Modifying the electrical continuity of the interfered structure	27
11	Inspection and maintenance	28
Annex A	(informative) Use of current probes to evaluate fluctuating stray current interference on cathodically protected structures	29
Annex B	(informative) Determining the relevant position for placing reference electrodes, coupons and probes in case of any conductive coupling caused by stray currents	32
Annex C	(informative) Operating principles of electrical resistance probes	39
Annex D	(informative) Geomagnetic interference	40
Annex E	(informative) High voltage direct current interference	49
Annex F	(informative) Alternating Current Interference	51
Annex G	(informative) Tidal Effects	56
Annex H	(informative) Photovoltaic interference	57
Annex I	(informative) Modelling the effects of stray current interference on cathodically protected pipelines	60
Annex J	(informative) Assessment of the corrosion risk for steel in concrete or for cathodically protected structures under time variant interference conditions	64
Annex K	(informative) Principles of anodic and cathodic interference	69
	Bibliography	72