

# ISO 24200:2022-05 (E)

## Petroleum, petrochemical and natural gas industries - Bulk material for offshore projects - Pipe support

---

| <b>Contents</b>           |   | <b>Page</b> |
|---------------------------|---|-------------|
| Foreword .....            |   | iv          |
| Introduction .....        |   | v           |
| <b>1</b>                  | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>                  | <b>Normative references .....</b>   | <b>1</b>    |
| <b>3</b>                  | <b>Terms, definitions and abbreviated terms .....</b>                     | <b>1</b>    |
| <b>3.1</b>                | <b>Terms and definitions .....</b>  | <b>1</b>    |
| <b>3.2</b>                | <b>Abbreviated terms .....</b>  | <b>3</b>    |
| <b>4</b>                  | <b>General .....</b>  | <b>4</b>    |
| <b>5</b>                  | <b>Support selection guideline .....</b>                                  | <b>4</b>    |
| <b>6</b>                  | <b>Design and material requirements .....</b>                             | <b>5</b>    |
| <b>6.1</b>                | <b>Clamped shoe .....</b>   | <b>5</b>    |
| <b>6.1.1</b>              | <b>Key parameters .....</b>   | <b>5</b>    |
| <b>6.1.2</b>              | <b>Size/Dimension .....</b>   | <b>5</b>    |
| <b>6.1.3</b>              | <b>Material .....</b>   | <b>7</b>    |
| <b>6.1.4</b>              | <b>Application .....</b>  | <b>7</b>    |
| <b>6.2</b>                | <b>Welded shoe .....</b>  | <b>8</b>    |
| <b>6.2.1</b>              | <b>Key parameters .....</b>   | <b>8</b>    |
| <b>6.2.2</b>              | <b>Size/Dimension .....</b>   | <b>8</b>    |
| <b>6.2.3</b>              | <b>Material .....</b>   | <b>12</b>   |
| <b>6.2.4</b>              | <b>Application .....</b>  | <b>12</b>   |
| <b>6.3</b>                | <b>U-bolt .....</b>   | <b>13</b>   |
| <b>6.3.1</b>              | <b>Key parameters .....</b>   | <b>13</b>   |
| <b>6.3.2</b>              | <b>Size/Dimension .....</b>   | <b>13</b>   |
| <b>6.3.3</b>              | <b>Application .....</b>  | <b>15</b>   |
| <b>6.4</b>                | <b>U-strap .....</b>  | <b>15</b>   |
| <b>6.4.1</b>              | <b>Key parameters .....</b>   | <b>15</b>   |
| <b>6.4.2</b>              | <b>Size/Dimension .....</b>   | <b>16</b>   |
| <b>6.4.3</b>              | <b>Application .....</b>  | <b>18</b>   |
| <b>6.5</b>                | <b>Bracing for branch connection .....</b>                                | <b>18</b>   |
| <b>6.5.1</b>              | <b>Key parameters .....</b>   | <b>18</b>   |
| <b>6.5.2</b>              | <b>Size/Dimension .....</b>   | <b>18</b>   |
| <b>6.5.3</b>              | <b>Application .....</b>  | <b>21</b>   |
| <b>6.6</b>                | <b>Trunnion and stanchion .....</b>                                       | <b>21</b>   |
| <b>6.6.1</b>              | <b>Trunnion .....</b>   | <b>21</b>   |
| <b>6.6.2</b>              | <b>Stanchion .....</b>  | <b>25</b>   |
| <b>6.7</b>                | <b>Guide, hold-down, guide and hold-down and line-stop support .....</b>  | <b>29</b>   |
| <b>6.7.1</b>              | <b>Guide .....</b>  | <b>29</b>   |
| <b>6.7.2</b>              | <b>Guide and hold-down .....</b>  | <b>31</b>   |
| <b>6.7.3</b>              | <b>Line-stop .....</b>  | <b>33</b>   |
| <b>6.8</b>                | <b>Guide, guide and hold-down and line-stop support - With hole .....</b> | <b>35</b>   |
| <b>6.8.1</b>              | <b>Guide .....</b>  | <b>35</b>   |
| <b>6.8.2</b>              | <b>Hold-down .....</b>  | <b>38</b>   |
| <b>6.8.3</b>              | <b>Guide and hold-down .....</b>  | <b>41</b>   |
| <b>6.8.4</b>              | <b>Line-stop .....</b>  | <b>45</b>   |
| <b>Bibliography .....</b> |   | <b>49</b>   |

**Bibliography ..... 49**