ISO 13503-8:2025-06 (E)

Oil and gas industries including lower carbon energy - Completion fluids and materials - Part 8: Measurement of properties of coated proppants used in hydraulic fracturing

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Sampling procedures for coated proppants **1**
4.1 General 1
4.2 Particle segregation 2
4.3 Equipment 2
4.4 Number of coated proppant samples — bulk 5
4.5 Sampling —bulk coated proppants 5
4.6 Sampling — bagged coated proppants 5
4.6.1 Bags up to 50 kg each 5
4.6.2 Totes, bulk bags or super-sags weighing up to 2 000 kg each 5

5 Samples handling and storage **6**
5.1 Sample reduction 6
5.2 Sample splitting 6
5.3 Sample record retention and storage 6

6 Performance test on precured coated proppants **6**
6.1 Dispersion rate 6
6.1.1 Purpose 6
6.1.2 Description 6
6.1.3 Equipment and materials 6
6.1.4 Sample preparation 7
6.1.5 Procedures 8
6.2 Wear loss 8
6.2.1 Purpose 8
6.2.2 Description 8
6.2.3 Equipment and materials 8
6.2.4 Procedures 9

7 Performance test on curable coated proppants **10**
7.1 Thermal tensile strength 10
7.1.1 Purpose 10
7.1.2 Description 10
7.1.3 Equipment and materials 10
7.1.4 Procedures 10
7.2 Curable melting point 11
7.2.1 Purpose 11
7.2.2 Description 11
7.2.3 Equipment and materials 11
7.2.4 Procedures 12
7.3 Compressive strength 12
7.3.1 Purpose 12
7.3.2 Description 12

7.3.3 Equipment and materials 12
7.3.4 Procedures 12
Annex A (Informative) **Sieve calibration** **14**
Annex B (Informative) **The wear device and formula** **17**
Annex C (Informative) **Core preparation unit** **19**
Annex D (Informative) **Core preparation method** **25**
Bibliography **28**