

ISO 24203:2025-12 (E)

Oil and gas industries including lower carbon energy - Bulk material for offshore projects - Schedule for architectural doors

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Design requirements for architectural doors	2
4.1	General information	2
4.1.1	Tag number	2
4.1.2	Room or area number	2
4.1.3	Room name	2
4.1.4	Drawing number	2
4.1.5	Internal or external door	2
4.1.6	Gastight door	2
4.1.7	Weathertight door	2
4.1.8	Fire rating	2
4.1.9	Blast overpressure	3
4.2	Door details	3
4.2.1	Clear opening and structure cut-out or wall cut-out	3
4.2.2	Opening operation	3
4.2.3	Frame fixing method	4
4.2.4	Door open direction	4
4.2.5	Leaf and frame material	5
4.2.6	Door finish method	5
4.2.7	Colour of door	5
4.2.8	Threshold type	6
4.2.9	Threshold height	6
4.2.10	Ventilation requirement	7
4.3	Accessories	8
4.3.1	Vision panel	8
4.3.2	Automatic closer	9
4.3.3	Hold open function	9
4.3.4	Doorstops	10
4.3.5	Magnetic door holder device	10
4.3.6	Panic bar	10
4.3.7	Kick plate and trolley protection plate	11
4.3.8	Flush bolts for double door	12
4.3.9	Eyebrow	13
4.3.10	Ramp	14
4.3.11	Other accessories	15
4.4	Locking system	16
4.4.1	Lock type	16
4.4.2	Padlock eye	16
4.4.3	Key side	17
4.5	Pneumatic system	17
4.5.1	General	17
4.5.2	Pneumatic key switch	17

4.5.3	Emergency air cylinder	18
4.5.4	Push button	19
4.5.5	Handle operation for pneumatic system	19
4.6	Other information	20
4.6.1	Noise rating	20
4.6.2	Mass of total door assembly	20
5	Schedule for architectural doors	20
5.1	General	20
5.2	Cabin	21
5.3	Office doors adjacent to a corridor	22
5.4	Private bathroom	23
5.5	Public toilet	24
5.6	Galley	26
5.7	Dining room	27
5.8	Laundry	28
5.9	Battery room	30
5.10	Uninterruptible power supply (UPS)	31
5.11	Workshop	32
5.12	Central control room (CCR)	34
5.13	High voltage room	35
	Bibliography	37