

# DIN EN ISO 14692-3:2005-07 (E)

## Petroleum and natural gas industries - Glass-reinforced plastics (GRP) piping - Part 3: System design (ISO 14692-3:2002); English version EN ISO 14692-3:2002

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1 Scope .....		7
2 Normative references .....		7
3 Terms and definitions .....		7
4 Symbols and abbreviated terms .....		7
5 Layout requirements .....		7
5.1 General .....		7
5.2 Space requirements .....		8
5.3 System supports .....		8
5.4 Isolation and access for cleaning .....		10
5.5 Vulnerability .....		10
5.6 Joint selection .....		11
5.7 Fire and blast .....		13
5.8 Control of electrostatic discharge .....		14
5.9 Galvanic corrosion .....		14
6 Hydraulic design .....		14
6.1 General .....		14
6.2 Flow characteristics .....		14
6.3 General velocity limitations .....		15
6.4 Erosion .....		15
6.5 Water hammer .....		16
6.6 Cyclic conditions .....		16
7 Structural design .....		16
7.1 General .....		16
7.2 Manufacturer's pressure rating .....		16
7.3 Qualified pressure .....		17
7.4 Factored qualified pressure .....		17
7.5 System design pressure .....		18
7.6 Loading requirements .....		19
7.7 Allowable displacements .....		21
7.8 Qualified stress .....		21
7.9 Factored stress .....		21
7.10 Limits of calculated stresses due to loading .....		22
7.11 Determination of failure envelope .....		23
8 Stress analysis .....		30
8.1 Analysis methods .....		30
8.2 Analysis requirements .....		30
8.3 External pressure/vacuum .....		31
8.4 Thermal loading .....		32
8.5 Stresses due to internal pressure .....		32
8.6 Stresses due to pipe support .....		33
8.7 Axial compressive load (buckling) .....		34
9 Fire performance .....		35
9.1 General .....		35
9.2 Fire endurance .....		36
9.3 Fire reaction .....		37
9.4 Fire-protective coatings .....		37

	Page
<b>10</b>	<b>Static electricity ..... 38</b>
<b>10.1</b>	<b>General..... 38</b>
<b>10.2</b>	<b>Classification code for control of electrostatic charge accumulation ..... 38</b>
<b>10.3</b>	<b>Mitigation options ..... 38</b>
<b>10.4</b>	<b>Design and documentation requirements..... 39</b>
<b>10.5</b>	<b>Pipes that contain a fluid with an electrical conductivity more than 10 000 pS/m ..... 41</b>
<b>10.6</b>	<b>Pipes that contain a fluid with an electrical conductivity less than 10 000 pS/m ..... 41</b>
<b>10.7</b>	<b>Pipes exposed to weak/moderate external electrostatic-generation mechanisms ..... 42</b>
<b>10.8</b>	<b>Pipes exposed to strong external electrostatic generation mechanisms ..... 42</b>
<b>10.9</b>	<b>Continuity of electrical path within piping system..... 43</b>
<b>10.10</b>	<b>Lightning strike ..... 43</b>
<b>11</b>	<b>Installer and operator documentation ..... 43</b>
<b>Annex A (informative)</b>	<b>Guidance for design of GRP piping system layout ..... 45</b>
<b>Annex B (informative)</b>	<b>Description and guidance on selection of jointing designs ..... 47</b>
<b>Annex C (informative)</b>	<b>Guidance on material properties and stress/strain analysis..... 52</b>
<b>Annex D (normative)</b>	<b>Guidance on flexibility analysis..... 54</b>
<b>Annex E (normative)</b>	<b>Calculation of support stresses for large-diameter liquid-filled pipe ..... 64</b>
<b>Annex F (informative)</b>	<b>Guidance on quantifying fire performance properties ..... 68</b>
<b>Annex G (informative)</b>	<b>Static electricity..... 73</b>
<b>Annex H (informative)</b>	<b>Inspection strategy ..... 81</b>
<b>Bibliography</b>	<b>..... 84</b>