ISO 14692-3:2002-12 (E)

Petroleum and natural gas industries - Glass-reinforced plastics (GRP) piping - Part 3: System piping

Contents

Page

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and abbreviated terms 1

5 Layout requirements 2
5.1 General 2
5.2 Space requirements 2
5.3 System supports 3
5.4 Isolation and access for cleaning 5
5.5 Vulnerability 5
5.6 Joint selection 6
5.7 Fire and blast 7
5.8 Control of electrostatic discharge 8
5.9 Galvanic corrosion 9

6 Hydraulic design 9
6.1 General 9
6.2 Flow characteristics 9
6.3 General velocity limitations 9
6.4 Erosion 10
6.5 Water hammer 10
6.6 Cyclic conditions 11

7 Structural design 11
7.1 General 11
7.2 Manufacturer's pressure rating 11
7.3 Qualified pressure 11
7.4 Factored qualified pressure 12
7.5 System design pressure 13
7.6 Loading requirements 14
7.7 Allowable displacements 16
7.8 Qualified stress 16
7.9 Factored stress 16
7.10 Limits of calculated stresses due to loading 17
7.11 Determination of failure envelope 18

8 Stress analysis 25
8.1 Analysis methods 25
8.2 Analysis requirements 25
8.3 External pressure/vacuum 26
8.4 Thermal loading 27
8.5 Stresses due to internal pressure 27
8.6 Stresses due to pipe support 28
8.7 Axial compressive load (buckling) 29

9 Fire performance 30
9.1 General 30
9.2 Fire endurance 31
9.3 Fire reaction 32
9.4 Fire-protective coatings 32

10 Static electricity 33
10.1 General 33
10.2 Classification code for control of electrostatic charge accumulation 33
10.3 Mitigation options 33
10.4 Design and documentation requirements 34
10.5 Pipes that contain a fluid with an electrical conductivity more than 10 000 pS/m 36
10.6 Pipes that contain a fluid with an electrical conductivity less than 10 000 pS/m 36
10.7 Pipes exposed to weak/moderate external electrostatic-generation mechanisms 37
10.8 Pipes exposed to strong external electrostatic generation mechanisms 37
10.9 Continuity of electrical path within piping system 38
10.10 Lightning strike 38

11 Installer and operator documentation 38

Annex A (informative) Guidance for design of GRP piping system layout 40

Annex B (informative) Description and guidance on selection of jointing designs 42

Annex C (informative) Guidance on material properties and stress/strain analysis 47

Annex D (normative) Guidance on flexibility analysis 49

Annex E (normative) Calculation of support stresses for large-diameter liquid-filled pipe 59

Annex F (informative) Guidance on quantifying fire performance properties 63

Annex G (informative) Static electricity 68

Annex H (informative) Inspection strategy 76

Bibliography 79