

# ISO 5263-3:2004-09 (E)

Pulps - Laboratory wet disintegration - Part 3: Disintegration of mechanical pulps at  
<größer => 85 °C

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| <b>Foreword</b>  | .....                                    | <b>iv</b>   |
| <b>1</b>   | <b>Scope</b> .....                       | <b>1</b>    |
| <b>2</b>   | <b>Normative references</b> .....        | <b>1</b>    |
| <b>3</b>   | <b>Definition</b> .....                  | <b>1</b>    |
| <b>4</b>   | <b>Apparatus</b> .....                   | <b>2</b>    |
| <b>5</b>   | <b>Preparation of test portion</b> ..... | <b>2</b>    |
| <b>6</b>   | <b>Procedure</b> .....                   | <b>3</b>    |
| <b>7</b>   | <b>Test report</b> .....                 | <b>4</b>    |
| <b>Annex A (normative) Construction of the Standard disintegrator</b> .....  |  | <b>5</b>    |
| <b>Annex B (normative) Checking the Standard disintegrator</b> .....         |  | <b>7</b>    |
| <b>Annex C (normative) Circulation disintegrator</b> .....                   |  | <b>8</b>    |
| <b>Annex D (informative) The effect of latency in mechanical pulps</b> ..... |  | <b>9</b>    |
| <b>Bibliography</b> .....  |  | <b>11</b>   |