

DIN EN ISO 3262-20:2021-07 (E)

Extenders - Specifications and methods of test - Part 20: Fumed silica (ISO 3262-20:2021)

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Requirements and test methods | 7 |
| 5 | Sampling | 7 |
| 6 | Determination of silica content | 7 |
| 6.1 | Principle | 7 |
| 6.2 | Reagents | 8 |
| 6.3 | Apparatus | 8 |
| 6.4 | Procedure | 8 |
| 6.4.1 | Number of determinations | 8 |
| 6.4.2 | Test portion | 8 |
| 6.4.3 | Determination | 8 |
| 6.5 | Expression of results | 9 |
| 6.6 | Precision | 9 |
| 7 | Determination of aluminium oxide, titanium (IV) oxide and iron (III) oxide contents by spectrometry | 9 |
| 7.1 | Principle | 9 |
| 7.2 | Reagents and materials | 9 |
| 7.3 | Apparatus | 10 |
| 7.4 | Procedure | 11 |
| 7.4.1 | Preparation of standard matching solutions | 11 |
| 7.4.2 | Spectrometric measurement | 11 |
| 7.4.3 | Calibration graph | 12 |
| 7.4.4 | Preparation of the test solution | 12 |
| 7.4.5 | Determination of aluminium, titanium and iron | 12 |
| 7.4.6 | Determination of the total loss on ignition | 12 |
| 7.5 | Expression of results | 13 |
| 7.5.1 | Calculation of the concentration of each element | 13 |
| 7.5.2 | Calculation of the oxide content for each element | 13 |
| 7.6 | Precision | 14 |
| 8 | Determination of carbon content | 14 |
| 8.1 | Principle | 14 |
| 8.2 | Reagents and materials | 14 |
| 8.3 | Apparatus | 15 |
| 8.4 | Procedure | 15 |
| 8.4.1 | Preparation of apparatus | 15 |
| 8.4.2 | Calibration | 15 |
| 8.4.3 | Determination | 15 |
| 8.5 | Expression of results | 15 |

| | | |
|-------|---|----|
| 8.6 | Precision | 16 |
| 9 | Determination of chloride content | 16 |
| 9.1 | Principle | 16 |
| 9.2 | Reagents | 16 |
| 9.3 | Apparatus | 16 |
| 9.4 | Procedure | 17 |
| 9.4.1 | Number of determinations | 17 |
| 9.4.2 | Test portion | 17 |
| 9.4.3 | Determination | 17 |
| 9.5 | Expression of results | 17 |
| 9.6 | Precision | 18 |
| 10 | Test report | 18 |