

# ISO 22159:2007-05 (E)

## Personal equipment for protection against falls - Descending devices

---

| <b>Contents</b>              |  | <b>Page</b> |
|------------------------------|--|-------------|
| Foreword .....               |  | iv          |
| Introduction .....           |  | v           |
| <b>1</b>                     | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>                     | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>                     | <b>Terms, definitions and classifications .....</b>  | <b>1</b>    |
| <b>3.1</b>                   | <b>Terms and definitions .....</b>   | <b>1</b>    |
| <b>3.2</b>                   | <b>Classifications .....</b>   | <b>3</b>    |
| <b>4</b>                     | <b>Requirements .....</b>  | <b>8</b>    |
| <b>4.1</b>                   | <b>General .....</b>   | <b>8</b>    |
| <b>4.2</b>                   | <b>Descent lines: basic requirements .....</b>   | <b>8</b>    |
| <b>4.3</b>                   | <b>Descent line stopper .....</b>  | <b>9</b>    |
| <b>4.4</b>                   | <b>Descent line residual static strength .....</b>   | <b>10</b>   |
| <b>4.5</b>                   | <b>Rated loads .....</b>   | <b>10</b>   |
| <b>4.6</b>                   | <b>Holding load .....</b>  | <b>11</b>   |
| <b>4.7</b>                   | <b>Static strength .....</b>   | <b>11</b>   |
| <b>4.8</b>                   | <b>Dynamic performance .....</b>   | <b>12</b>   |
| <b>4.9</b>                   | <b>Descent energy .....</b>  | <b>12</b>   |
| <b>4.10</b>                  | <b>Descent velocity .....</b>  | <b>13</b>   |
| <b>4.11</b>                  | <b>Temperature rise .....</b>  | <b>13</b>   |
| <b>4.12</b>                  | <b>Special requirements for descending devices class D .....</b>                           | <b>14</b>   |
| <b>4.13</b>                  | <b>Function .....</b>  | <b>14</b>   |
| <b>4.14</b>                  | <b>Corrosion resistance .....</b>  | <b>14</b>   |
| <b>4.15</b>                  | <b>Conditioning .....</b>  | <b>15</b>   |
| <b>4.16</b>                  | <b>Marking and information .....</b>   | <b>15</b>   |
| <b>5</b>                     | <b>Test methods .....</b>  | <b>15</b>   |
| <b>5.1</b>                   | <b>Test apparatus .....</b>  | <b>15</b>   |
| <b>5.2</b>                   | <b>General .....</b>   | <b>17</b>   |
| <b>5.3</b>                   | <b>Conditioning .....</b>  | <b>18</b>   |
| <b>5.4</b>                   | <b>Examination of design .....</b>   | <b>18</b>   |
| <b>5.5</b>                   | <b>Static tests .....</b>  | <b>19</b>   |
| <b>5.6</b>                   | <b>Dynamic performance .....</b>   | <b>24</b>   |
| <b>5.7</b>                   | <b>Descent energy, descent velocity, temperature rise .....</b>                            | <b>31</b>   |
| <b>5.8</b>                   | <b>Function tests .....</b>  | <b>34</b>   |
| <b>5.9</b>                   | <b>Corrosion resistance .....</b>  | <b>41</b>   |
| <b>6</b>                     | <b>Marking .....</b>   | <b>41</b>   |
| <b>7</b>                     | <b>Information supplied by the manufacturer .....</b>                                      | <b>42</b>   |
| <b>7.1</b>                   | <b>General .....</b>   | <b>42</b>   |
| <b>7.2</b>                   | <b>Instructions for use .....</b>  | <b>42</b>   |
| <b>7.3</b>                   | <b>Instructions for maintenance .....</b>  | <b>45</b>   |
| <b>7.4</b>                   | <b>Instructions for periodic detailed inspections .....</b>                                | <b>45</b>   |
| <b>7.5</b>                   | <b>Instructions for repair .....</b>   | <b>46</b>   |
| <b>7.6</b>                   | <b>Records .....</b>   | <b>46</b>   |
| <b>Annex A (informative)</b> | <b>Packaging .....</b>   | <b>47</b>   |
| <b>Annex B (informative)</b> | <b>Functional recommendations for the use of descending devices in the workplace .....</b> | <b>48</b>   |
| <b>Bibliography .....</b>    |  | <b>50</b>   |