

DIN EN 795:2012-10 (E)

Personal fall protection equipment - Anchor devices

Contents	Page
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Requirements	14
4.1 General	14
4.2 Materials	14
4.2.1 Metal parts	14
4.2.2 Rope and webbing	14
4.2.3 Connectors	15
4.3 Design and ergonomics	15
4.4 Specific requirements	15
4.4.1 Type A anchor devices	15
4.4.2 Type B anchor devices	15
4.4.3 Type C anchor devices	15
4.4.4 Type D anchor devices	16
4.4.5 Type E anchor devices	16
4.5 Marking and information	17
5 Test methods	17
5.1 General	17
5.2 Test arrangement and apparatus	18
5.2.1 Test lanyard and determination of free fall distance	18
5.2.2 Dynamic strength and integrity test apparatus for types A, B, C and D anchor devices	19
5.2.3 Static strength test apparatus	19
5.2.4 Dynamic performance test apparatus for type E anchor devices	19
5.3 Type A anchor devices	20
5.3.1 General	20
5.3.2 Deformation	20
5.3.3 Dynamic strength and integrity	20
5.3.4 Static strength	21
5.4 Type B anchor devices	21
5.4.1 General	21
5.4.2 Deformation	21
5.4.3 Dynamic strength and integrity	21
5.4.4 Static strength	24
5.5 Type C anchor devices	26
5.5.1 General	26
5.5.2 Deformation	27
5.5.3 Dynamic strength and integrity	27
5.5.4 Static strength	31
5.6 Type D anchor devices	31
5.6.1 General	31
5.6.2 Deformation	31
5.6.3 Dynamic strength and integrity	31
5.6.4 Static strength	33

5.7	Type E anchor devices	33
5.7.1	Deformation	33
5.7.2	Dynamic performance	33
5.7.3	Post arrest suspension	34
5.7.4	Static strength	34
5.8	Corrosion resistance	34
6	Marking	35
7	Information supplied by the manufacturer	35
	Annex A (informative) Information on installation documentation and periodic examination	37
A.1	Information on installation to be supplied by the manufacturer	37
A.2	Guidance on documentation to be supplied after an installation	37
A.3	Guidance on periodic examination procedure	40
	Annex B (informative) Significant technical changes between this European Standard and the Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC	43
	Bibliography	44
	Figures	
	Figure 1 -- Examples of anchor systems that include an anchor device	8
	Figure 2 -- Examples of anchor systems that are not covered by this European Standard	9
	Figure 3 -- Example of a type A anchor device with a structural anchor	11
	Figure 4 -- Example of a type A anchor device with a fixing element	11
	Figure 5 -- Examples of type B anchor devices	12
	Figure 6 -- Example of a type C anchor device	13
	Figure 7 -- Example of a type D anchor device	13
	Figure 8 -- Example of a type E anchor device	13
	Figure 9 -- Bowline knot	18
	Figure 10 -- Test lanyard for dynamic strength and integrity tests and dynamic performance tests ..	19
	Figure 11 -- Example of a dynamic performance test apparatus for type E anchor devices	20
	Figure 12 -- Dynamic test for type B anchor devices with legs (e.g. a tripod) and an anchor point(s) not on a leg	23
	Figure 13 -- Dynamic test for type B anchor devices with legs (e.g. a tripod) and an anchor point on a leg	24
	Figure 14 -- Static strength test for type B anchor device with legs (e.g. a tripod) and a central anchor point	25
	Figure 15 -- Static strength test for type B anchor device with legs (e.g. a tripod) and an anchor point on a leg	26
	Figure 16 -- Example of a single-span type C anchor device test arrangement	28
	Figure 17 -- Example of a multi-span type C anchor device test arrangement without a corner	30
	Figure 18 -- Example of a multi-span type C anchor device test arrangement with a corner	30

Figure 19 -- Example of a type D anchor device test arrangement including a cantilever	32
Figure 20 -- Example of a type D anchor device test arrangement including a rigid anchor line joint or junction and a corner anchor	33
Figure A.1 -- Example of an installation plan	39
Figure A.2 -- Example of periodic examination procedure	40
Tables Table B.1 -- Significant technical changes	41
Table ZA.1 -- Correspondence between this European Standard and Directive 89/686/EEC	43