

DIN EN 1621-4:2013-04 (E)

Motorcyclists' protective clothing against mechanical impact - Part 4: Motorcyclists' inflatable protectors - Requirements and test methods

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Requirements	8
4.1 General	8
4.2 Innocuousness	9
4.2.1 Colour	9
4.2.2 Hard components	9
4.2.3 Temperature exposure evaluation	9
4.3 Zones of protection	9
4.4 Intervention time	9
4.5 Duration time	9
4.6 Retention of the inflatable protector	9
4.7 Impact attenuation	10
4.8 Sizing and size marking	10
4.9 Ergonomic requirements	10
4.10 Trigger system function	10
4.10.1 Activation force	10
4.10.2 Activation energy	10
4.10.3 Connection of airbag system to motorcycle	10
5 Sampling	10
6 Test methods	11
6.1 Preconditioning and testing atmosphere	11
6.2 Innocuousness	11
6.2.1 Colour fastness to water	11
6.2.2 Protection from hard components	11
6.2.3 Temperature exposure evaluation (applicable only for hot gas generators)	11
6.3 Measurement and marking of zones of protection	11
6.4 Intervention time	11
6.4.1 General	11
6.4.2 Determination of the activation time	11
6.4.3 Determination of the inflation time	13
6.5 Determination of duration of inflated status	13
6.6 Impact attenuation	13
6.7 Ergonomic tests	13
6.7.1 General	13
6.7.2 Tests	14
6.8 Evaluation of the function of the mechanism of activation	14
6.8.1 Evaluation of activation force	14
6.8.2 Evaluation of the activation energy	14
6.8.3 Connection to the motorcycle	14
6.9 Uncertainty	14

7	Test results	15
8	Test report	16
9	Marking	16
10	Information supplied by the manufacturer	17
	Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC	18
	Figures Figure 1 -- Trigger cable fixed to the motorbike behind the biker	12
	Figure 2 -- Trigger cable is fixed to the motorbike in front of the biker	12
	Figure 3 -- Example of graphical symbol	16
	Tables Table 1 -- Summary of the requirements	8
	Table 2 Transmitted force and performance levels	10