

DIN EN ISO 20346:2014-09 (E)

Personal protective equipment - Protective footwear (ISO 20346:2014)

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Classification and designs | 10 |
| 5 | Basic requirements for protective footwear | 11 |
| 5.1 | General | 11 |
| 5.2 | Design | 14 |
| 5.2.1 | General | 14 |
| 5.2.2 | Height of upper | 14 |
| 5.2.3 | Seat region | 15 |
| 5.3 | Whole footwear | 15 |
| 5.3.1 | Sole performance | 15 |
| 5.3.2 | Toe protection | 15 |
| 5.3.3 | Leakproofness | 16 |
| 5.3.4 | Specific ergonomic features | 17 |
| 5.3.5 | Slip resistance requirement | 17 |
| 5.3.6 | Innocuousness | 18 |
| 5.4 | Upper | 18 |
| 5.4.1 | General | 18 |
| 5.4.2 | Thickness | 18 |
| 5.4.3 | Tear strength | 18 |
| 5.4.4 | Tensile properties | 19 |
| 5.4.5 | Flexing resistance | 19 |
| 5.4.6 | Water vapour permeability and coefficient | 19 |
| 5.4.7 | pH value | 19 |
| 5.4.8 | Hydrolysis | 19 |
| 5.4.9 | Chromium VI content | 19 |
| 5.5 | Vamp and quarter lining | 20 |
| 5.5.1 | Tear strength | 20 |
| 5.5.2 | Abrasion resistance | 20 |
| 5.5.3 | Water vapour permeability and coefficient | 20 |
| 5.5.4 | pH value | 20 |
| 5.5.5 | Chromium VI content | 20 |
| 5.6 | Tongue | 20 |
| 5.6.1 | Tear strength | 20 |
| 5.6.2 | pH value | 21 |
| 5.6.3 | Chromium VI content | 21 |
| 5.7 | Insole and insock | 21 |
| 5.7.1 | Thickness | 21 |
| 5.7.2 | pH value | 21 |
| 5.7.3 | Water absorption and desorption | 21 |
| 5.7.4 | Abrasion resistance | 21 |
| 5.7.5 | Chromium VI content | 21 |
| 5.8 | Outsole | 22 |
| 5.8.1 | Design | 22 |
| 5.8.2 | Tear strength | 22 |

| | | |
|--|---|----|
| 5.8.3 | Abrasion resistance | 22 |
| 5.8.4 | Flexing resistance | 22 |
| 5.8.5 | Hydrolysis | 23 |
| 5.8.6 | Interlayer bond strength | 23 |
| 6 | Additional requirements for protective footwear | 23 |
| 6.1 | General | 23 |
| 6.2 | Whole footwear | 24 |
| 6.2.1 | Penetration resistance | 24 |
| 6.2.2 | Electrical properties | 25 |
| 6.2.3 | Resistance to inimical environments | 25 |
| 6.2.4 | Energy absorption of seat region | 25 |
| 6.2.5 | Water resistance | 26 |
| 6.2.6 | Metatarsal protection | 26 |
| 6.2.7 | Ankle protection | 26 |
| 6.2.8 | Cut resistance footwear | 26 |
| 6.3 | Upper -- Water penetration and absorption | 27 |
| 6.4 | Outsole | 27 |
| 6.4.1 | Resistance to hot contact | 27 |
| 6.4.2 | Resistance to fuel oil | 28 |
| 7 | Marking | 28 |
| 8 | Information to be supplied | 29 |
| 8.1 | General | 29 |
| 8.2 | Electrical properties | 30 |
| 8.2.1 | Conductive footwear | 30 |
| 8.2.2 | Antistatic footwear | 30 |
| 8.3 | Insocks | 31 |
| Annex A (normative) Hybrid footwear | | 32 |
| A.1 | General | 32 |
| A.2 | Height | 32 |
| A.3 | Area A | 32 |
| A.4 | Area B | 32 |
| A.5 | Water resistance | 32 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC Personal Protective Equipment | | 34 |
| Bibliography | | 36 |