

ISO 11999-3:2015-06 (E)

PPE for firefighters - Test methods and requirements for PPE used by firefighters who are at risk of exposure to high levels of heat and/or flame while fighting fires occurring in structures - Part 3: Clothing

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 3 |
| 4 | Clothing requirements | 3 |
| 4.1 | General | 3 |
| 4.2 | Clothing configuration | 3 |
| 4.3 | Multi-layer clothing assemblies | 3 |
| 4.4 | Component assembly | 3 |
| 4.5 | Attachment of interlining and innermost layers | 3 |
| 4.6 | Extension of interlining and innermost layers | 4 |
| 4.7 | Garment closure systems | 4 |
| 4.8 | Hardware | 4 |
| 4.9 | External pocket requirements | 4 |
| 4.10 | Garment sizing | 4 |
| 4.11 | Neck protection | 4 |
| 4.12 | Wrist protection | 4 |
| 4.13 | High-visibility materials | 5 |
| 4.13.1 | General | 5 |
| 4.13.2 | Option 1 -- Placement based on minimum area of coverage | 5 |
| 4.13.3 | Option 2 -- Placement based on standard pattern | 5 |
| 4.14 | Sampling | 7 |
| 4.14.1 | Samples | 7 |
| 4.14.2 | Sampling levels | 7 |
| 4.14.3 | Exposure surface | 7 |
| 4.15 | Pre-treatment | 7 |
| 4.15.1 | General | 7 |
| 4.15.2 | Pre-treatment by laundering or dry cleaning | 7 |
| 4.16 | Clothing -- Performance requirements | 8 |
| 4.17 | Flame and thermal resistance performance | 10 |
| 4.17.1 | General | 10 |
| 4.17.2 | Flame resistance (surface ignition) for performance level A1 | 11 |
| 4.17.3 | Flame resistance (bottom-edge ignition) for performance level A2 | 11 |
| 4.17.4 | Heat resistance | 11 |
| 4.17.5 | Heat transfer (flame exposure) | 12 |
| 4.17.6 | Heat transfer (radiant exposure) | 12 |
| 4.17.7 | Heat transfer (combined flame and radiant exposure) | 12 |
| 4.17.8 | Residual strength of material following radiant heat exposure | 13 |
| 4.17.9 | Conductive compressive heat resistance | 13 |
| 4.17.10 | Thread heat resistance | 14 |
| 4.18 | Strength and physical hazard resistance performance | 14 |
| 4.18.1 | Tensile strength | 14 |
| 4.18.2 | Tear strength | 14 |
| 4.18.3 | Seam strength (woven materials) | 14 |
| 4.18.4 | Seam strength (knit or stretch woven materials) | 14 |

| | | |
|------------------------------|--|-----------|
| 4.19 | Water and liquid resistance performance | 14 |
| 4.19.1 | General | 14 |
| 4.19.2 | Surface wetting | 15 |
| 4.19.3 | Water absorption resistance | 15 |
| 4.19.4 | Water penetration resistance | 15 |
| 4.19.5 | Liquid penetration resistance (runoff method) for performance level c1 | 16 |
| 4.19.6 | Liquid penetration pressure resistance (hydrostatic method) for performance level c2 .. | 16 |
| 4.19.7 | Viral penetration resistance for performance level c2 | 16 |
| 4.19.8 | Overall garment liquid penetration resistance for performance level c2 | 17 |
| 4.19.9 | Light degradation resistance for performance level c2 | 17 |
| 4.20 | Thermal comfort performance | 17 |
| 4.20.1 | General | 17 |
| 4.20.2 | Water vapour resistance | 17 |
| 4.20.3 | Total heat loss | 18 |
| 4.21 | Additional requirements | 18 |
| 4.21.1 | Cleaning shrinkage resistance | 18 |
| 4.21.2 | Hardware corrosion resistance | 18 |
| 4.21.3 | Photometric requirements of high-visibility retroreflective/combined performance materials used on garments | 18 |
| 4.21.4 | Colour requirements of high-visibility fluorescent/combined performance materials used on garments | 19 |
| 4.21.5 | Heat resistance of high-visibility materials used on garments | 20 |
| 4.21.6 | Flame spread of high-visibility materials used on garments | 20 |
| 4.21.7 | Protective wristlets | 20 |
| 4.21.8 | Optional clothing test using an instrumented manikin | 20 |
| 4.21.9 | Optional drag rescue device (DRD) | 20 |
| 5 | Compatibility | 21 |
| 6 | Marking | 21 |
| 7 | Manufacturer's information | 21 |
| Annex A (informative) | Comparison of performance requirements for clothing | 22 |