ISO 11393-1:2018 (E)

Protective clothing for users of hand-held chainsaws — Part 1: Test rig for testing resistance to cutting by a chainsaw

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Principles

5 Test rig

- 5.1 General
- 5.2 Power unit and connecting device
- 5.3 Saw unit
- 5.3.1 General
- 5.3.2 Components of saw unit
- 5.3.2.1 Guide bar
- 5.3.2.2 Chain drive sprocket
- 5.3.2.3 Moment of inertia of rotating parts
- 5.3.2.4 Saw chain
- 5.3.2.5 Lubrication system
- 5.3.3 Release system
- 5.3.4 Instrumentation
- 5.3.5 Fixture for saw unit
- 5.4 Calibration pad mount
- 5.5 Calibration pad fixture device

6 Calibration materials

7 Calibration of the test rig

- 7.1 General
- 7.2 Starting up the rig
- 7.3 Chain stopping time
- 7.4 Measurement of chain speed
- 7.5 Calibration with clogging material (pads)
- 7.5.1 Conditioning of the saw chain
- 7.5.2 Attachment of calibration pad
- 7.5.3 Cut test

Annex A (normative) Supplementary information on calibration pads

Annex B (normative) Testing of calibration pads at 19 m/s and 21 m/s

Annex C (informative) Method for checking the moment of inertia around pivot

Page count: 14